



2013 Jeep® Patriot CANADIAN SPECIFICATIONS

All dimensions are in millimetres (inches) unless otherwise noted.

All dimensions are measured at curb weight with standard wheels and tires unless otherwise noted.

NOTE: Information shown is correct at time of publication and is subject to change.

GENERAL INFORMATION

Body Style	Sport-utility vehicle
Assembly Plant	Belvidere, Illinois, U.S.A.
EnerGuide Vehicle Class	Special Purpose
Introduction Date	December 2006 as a 2007 model

ENGINE: 2.0-LITRE DOHC 16-VALVE I-4 WITH DUAL VVT

Availability	Available on 2WD Patriot Sport and North
Type and Description	Four cylinders in-line, tuned intake manifold with electronic active charge motion control valves, dual counter-rotating balance shafts
Displacement, cu. cm (cu. in.)	1998 (121.9)
Bore x Stroke	86 x 86 (3.39 x 3.39)
Valve System	Chain-driven DOHC, 16 valves, electronically controlled dual variable valve timing (VVT), direct-acting shimless mechanical bucket tappets
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	High-pressure die-cast aluminum block with dry iron liners, cast-aluminum cylinder head, cast-aluminum ladder frame, forged steel crankshaft
Compression Ratio	10.5:1
Power	158 bhp @ 6,400 rpm
Torque	141 lb.-ft. @ 5,000 rpm
Maximum Engine Speed	6,750 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity, L (qt.)	4.7 (5.0) SAE 5W/20
Coolant Capacity, L (qt.)	6.8 (7.2)
Emission Controls	Single catalytic converter, dual heated oxygen sensors and engine features
Smog-forming Pollution, g/km (g/mile)	0.56 (0.9)
2012 EnerGuide Fuel Economy L/100 km (mpg) - City/Hwy	9.1 (31)/6.8 (42)— 2WD with five speed manual transaxle 9.0 (31)/7.3 (39) — 2WD with continuously variable transmission (CVT)

ENGINE: 2.4-LITRE DOHC 16-VALVE I-4 WITH DUAL VVT

Availability	Standard on Sport, North and Limited (4x2 and 4x4)
Type and Description	Four-cylinder in-line, tuned intake manifold with electronic active charge motion control valves, dual counter-rotating balance shafts
Displacement, cu. cm (cu. in.)	2360 (144)
Bore x Stroke	88 x 97 (3.46 x 3.82)
Valve System	Chain-driven DOHC, 16 valves, electronically controlled dual VVT, direct-acting shimless mechanical bucket tappets
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	High-pressure die-cast aluminum block with dry iron liners, cast-aluminum cylinder head, cast-aluminum ladder frame, forged steel crankshaft
Compression Ratio	10.5:1
Power	172 bhp @ 6,000 rpm
Torque	165 lb.-ft. @ 4,400 rpm
Maximum Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity, L (qt.)	4.7 (5.0) SAE 5W/20
Coolant Capacity, L (qt.)	6.8 (7.2)
Emission Controls	Single catalytic converter — 2WD Dual catalytic converter — 4WD Dual heated oxygen sensors and engine features
Smog-forming Pollution, g/km (g/mile)	0.56 (0.9)
Maximum Gross Trailer Weight, kg (lb.)	454 (1000) 907 (2000) — with Freedom Drive II® package, trailer-tow prep group
2012 EnerGuide Fuel Economy L/100 km (mpg) - City/Hwy	9.0 (31)/7.0 (40) — 2WD with five-speed manual transaxle 9.6 (29)/7.4 (38) — 2WD with CVT2 9.2 (31)/7.2 (39) — 4WD with five-speed manual transaxle 9.9 (29)/7.7 (37) — 4WD with CVT2

TRANSAXLE: MAGNA DRIVELINE T355 5-SPEED

Availability	Standard — 2.0L engine Standard — 2.4L engine
Description	5-speed, overdrive, synchronized in all forward ratios, cable-operated, 3-plane shifter
Gear Ratios	
1 st	3.77
2 nd	2.16
3 rd	1.41
4 th	1.026
5 th	0.72
Reverse	3.417
Final-drive Ratio	4.12
Overall Top-gear	2.97



TRANSAXLE: AUTOMATIC JATCO MODEL CVT2 WITH AUTO/STICK™

Availability	Optional — 2.0L engine Optional — 2.4L engine
Description	Continuously variable ratio, lockup torque converter, electronic controls
Gear Ratios	
Forward	2.349:1 to 0.394:1 continuously variable
Reverse	1.75:1
Final-drive Ratio	6.12:1 (2.0L), 5.798:1 (2.4L)
Overall Top-gear Ratio	2.411:1 (2.0L); 2.28 (2.4L)

TRANSAXLE: AUTOMATIC JATCO MODEL CVT2L

Availability	Optional on 4WD with 2.4L engine
Description	Continuously variable ratio, lockup torque converter, electronic controls
Gear Ratios	
Forward	2.349:1 to 0.394:1 continuously variable
Reverse	1.75:1
Final-drive Ratio	8.135:1
Overall Top-gear Ratio	3.21:1
Effective Maximum Low-gear Ratio	19.11:1

DRIVETRAIN

Front-wheel Drive	
Availability	Standard
Front Differential	Open
Four-wheel Drive	
Availability	Optional
Type	Electronically-controlled coupling (ECC) with four-wheel drive Lock
Rear Differential	Open

ELECTRICAL SYSTEM

Alternator	120-amp 140-amp with CVT2L
Battery	525 CCA, maintenance-free



DIMENSIONS AND CAPACITIES

Wheelbase	2635 (103.7)
Track — Front	1520 (59.8)
Track — Rear	1520 (59.8)
Overall Length	4414 (173.8)
Overall Width	1757 (69.2)
Overall Height	1663 (65.5) 2WD, 1,696 (66.8) 4x4
Overhang — Front	885 (34.7)
Overhang — Rear	894 (35.1)
Approach Angle with P215/60/R17 Tire	26.4°
Breakover Angle with P215/60/R17 Tire	20.9°
Departure Angle with P215/60/R17 Tire	28.5°
Ground Clearance with P215/60/R17 Tire	205 (8.1)
Approach Angle with Freedom Drive II Off-Road Package including P215/65/R17 Tire	29.0°
Breakover Angle with Freedom Drive II Off-Road Package including P215/65/R17 Tire	23.7°
Departure Angle with Freedom Drive II Off-Road Package including P215/65/R17 Tire	33.9°
Ground Clearance with Freedom Drive II Off-Road Package including P215/65/R17 Tire	231 (9.1)
Aero (CdA)	10.4 — 2WD 11.0 — 4WD
Curb Weight, kg (lb.) Estimated	1411 (3111) — Sport 2WD, 2.0L MTX 1480 (3263) — Sport 4WD, 2.4L MTX 1446 (3187) — Limited 2WD, 2.4L MTX 1511 (3331) — Limited 4WD, 2.4L MTX
Weight Distribution, per cent F/R	58/42 — 2WD 57/43 — 4WD
Fuel Tank Capacity, L (gal.)	51.5 (11.3) — 2WD 51.1 (11.2) — 4WD



ACCOMMODATIONS

Seating Capacity — F/R	2/3
Front	
Head Room without Sunroof	1040 (41.0)
Leg Room	1032 (40.6)
Shoulder Room	1385 (54.5)
Hip Room	1329 (52.3)
Seat Travel	260 (10.2)— driver 260 (10.2)— passenger
Recliner Angle Range	Up to 88° — driver 76° fold-flat/88° non-fold-flat — passenger
Front Volume Index, L (cu. ft.)	1481 (52.3)
Rear	
Head Room	1014 (39.9)
Leg Room	1001 (39.4)
Knee Clearance	44.1 (1.7)
Shoulder Room	1372 (54.0)
Hip Room	1295 (51.0)
Rear Seat Volume Index, L (cu. ft.)	1390 (49.1)
Interior Volume, L (cu. ft.)	2956 (104.4)
Cargo Volume Indexes	
Rear Seats Up, L (cu. ft.)	651 (23.0)
Rear Seats Folded, L (cu. ft.)	1515 (53.5)
Interior Volume Index, L (cu. ft.)	3522 (124.4)
Trunk Lift-over Height	780 (30.7)
Cargo Volume with Front Passenger Fold-flat seat and Rear seat folded L (cu. ft.)	1795 (63.4)
Minimum Cargo Width at Liftgate Opening	988 (38.9)
Minimum Cargo Height at Liftgate Opening	656 (25.9)
Maximum Cargo Width at Liftgate Opening	1146 (45.1)
Maximum Cargo Height at Liftgate Opening	696 (27.4)
Distance Between Wheelhouse Interior Trim	965 (38.0)
BODY	
Layout	Transverse front-engine front-wheel drive or four-wheel drive
Construction	Unitized steel body



SUSPENSION

Front	Independent MacPherson strut, coil spring over gas-charged shock absorbers and stabilizer bar — Standard
Rear	Multi-link independent with coil springs, link-type stabilizer bar, gas-charged shock absorbers — Standard

STEERING

Type	Rack and pinion with hydraulic power assist
Overall Ratio	16.4:1
Turning Diameter (curb-to-curb)	With 16- or 17-in. wheels — 10.8 m (35.6 ft.)
Steering Turns (lock-to-lock)	With 16- or 17-in. wheels and tires — 2.88

WHEELS

Availability	Standard on Sport and North
Type and Material	Styled steel
Size	16 in. x 6.5 in.

Availability	Standard on Limited, Optional on Sport and North
Type and Material	Polished Aluminum
Size	17 in. x 6.5 in.

TIRES

Availability	Standard on Sport and North
Size and Type	P205/70R16 BSW All-season Touring
Manufacturer and Model	Goodyear Eagle LS2
Revs per km (mile)	470 (758)

Availability	Standard on Limited, Optional on Sport and North
Size and Type	P215/60R17 BSW All-season Touring
Manufacturer and Model	Firestone Affinity
Revs per km (mile)	479 (771)

Availability	Included with Freedom Drive II Off-Road Package and Tire and Wheel Group
Size and Type	P215/65R17 OWL All-terrain
Manufacturer and Model	Goodyear Wrangler GTA 03
Revs per km (mile)	462 (743)



BRAKES

Availability	Standard on Sport and North 4x2
Front	
Size and Type	11.5 x 1.0 in. (294 x 26 mm) vented disc with 2.2 in. (57 mm) single-piston floating caliper
Swept Area, sq. cm (sq. in.)	1442 (223)
Rear	
Size and Type	9.0 x 1.38 in. (229 x 35) drums
Swept Area, sq. cm (sq. in.)	503.6 (78.1)
Power-assist Type	254 (10) single-diaphragm vacuum
Anti-lock Brake System (ABS)	Standard
Electronic Stability Control (ESC)	Standard
Availability	Standard on Sport 4x4, North 4x4 and Limited 4x2 and 4x4
Front	
Size and Type	11.5 x 1.0 in. (294 x 26 mm) vented disc with 2.2 in. (57 mm) single-piston floating caliper
Swept Area, sq. cm (sq. in.)	1442 (223)
Rear	
Size and Type	10.3 x 0.39 in. (262 x 10) solid disc with 1.4 in. (35 mm) single-piston floating caliper
Swept Area, sq. cm (sq. in.)	894.6 (138.64)
Power-assist Type	254 (10) single-diaphragm vacuum
Anti-lock Brakes with On- and Off-road Calibrations	Standard
Electronic Stability Control (ESC)	Standard
Hill-start Assist (HSA)	Standard with manual transmission and Freedom Drive II Off-Road Package
Off-road Brake-traction Control System (BTCS)	Included with Freedom Drive II Off-Road Package
Hill-descent Control (HDC)	Included with Freedom Drive II Off-Road Package

• • •