



Jeep® GRAND CHEROKEE SRT8

Canadian Specifications

2013 Jeep® Grand Cherokee SRT8® CANADIAN SPECIFICATIONS

All dimensions are in millimetres (inches) unless otherwise noted.

All dimensions are measured at curb weight with standard wheels and tires unless otherwise noted.

NOTE: Information shown is correct at time of publication and is subject to change.

GENERAL INFORMATION

Body Style	Four-door sport-utility vehicle
Construction	Steel uniframe
Assembly Plant	Detroit, Michigan U.S.A.
EnerGuide Vehicle Class	Multi-purpose vehicle
Introduction	Summer 2011 as a 2012 model

ENGINE: 6.4-LITRE HEMI® V8 WITH FUELSAVER MDS TECHNOLOGY

Availability	Standard
Type and Description	90-degree V-type, liquid-cooled
Displacement, cu. cm (cu. in.)	6424 (392)
Bore x Stroke	103.9 x 94.5 (4.09 x 3.72)
Valve System	Pushrod-operated overhead valves, 16 valves with sodium-filled exhaust valves and hollow stem intake valves, 16 conventional hydraulic lifters, all with roller tips
Fuel Injection	Sequential, multi-port, electronic, returnless; automatic features Fuel Saver mode
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.9:1
Power	470 hp at 6,000 rpm
Torque	465 lb.-ft. at 4,300 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Premium 91 octane (R+M)/2 — recommended
Oil Capacity, L (qt.)	6.6 (7)
Coolant Capacity, L (qt.)	13.25 (14)
Factory Oil Fill	0W-40 Full Synthetic
Emission Controls	Dual close-coupled three-way catalytic converters, quad-heated oxygen sensors and internal engine features
EnerGuide Fuel Economy L/100 km (mpg) – City/Hwy	17.1 (17)/11.4 (25)
Assembly Plant	Saltillo, Mexico



Jeep® GRAND CHEROKEE SRT8

Canadian Specifications

TRANSMISSION: W5A580 FIVE-SPEED AUTOMATIC

Availability	Standard with 6.4-litre HEMI® engine
Description	Auto/Stick™ driver interactive manual control and electronically modulated torque converter clutch
Gear Ratios	
1 st	3.59
2 nd	2.19
3 rd	1.41
4 th	1.00
5 th	0.83
Reverse	3.16
Final Drive Ratio	3.70:1 – ZF Electronic Limited Slip Differential
Overall Top Gear	3.07

TRANSFER CASE: MP 3010

Availability	Standard with 6.4-litre HEMI engine
Type	Single-speed, electronic proportioning
Operating Modes	Full-time 4WD
Torque Split, Front/Rear	Variable – 40/60 Auto, 50/50 Snow, and 35/65 Sport and Track

FRONT AXLES

Differential Type	Conventional
Availability	Standard with 6.4-litre HEMI engine
Ring Gear Diameter	195 (7.7)
Axle Ratio	3.70:1

REAR AXLES

Differential Type	Electronic Limited Slip Differential (ELSD)
Availability	Standard with 6.4-litre HEMI engine
Ring Gear Diameter	230 (9)
Axle Ratio	3.70:1

ELECTRICAL SYSTEM

Alternator	Standard 220-amp
Battery	Group 65 maintenance-free 750CCA



Jeep® GRAND CHEROKEE SRT8

Canadian Specifications

DIMENSIONS AND CAPACITIES

Wheelbase	2915 (114.8)
Track, Front	1618 (63.7)
Track, Rear	1633 (64.3)
Overall Length	4859 (191.3)
Overall Width (Width at Mirrors)	2156 (84.9)
Body Width	1958 (77.1)
Overall Height (at Roof Rail/at Antenna)	1756 (69.1)/1952 (76.9)
Load Floor Height	823 (32.4)
Sill Step Height	527 (20.7)
Minimum Ground Clearance	211 (8.3)
Chassis (Fuel Tank)	230 (9)
Front Axle	228 (8.97)
Rear Axle	228 (8.99)
Approach Angle, Degrees	18.45
Ramp Breakover Angle, Degrees	17.84
Departure Angle, Degrees	21.9
Frontal Area, sq. m (sq. ft.)	2.93 (31.5)
Drag Coefficient	.39
Aero CdA	12.2 (Cd x cross-sectional area)
Fuel Tank Capacity, L (gal.)	93.1 (20.5)

ACCOMMODATIONS

Seating Capacity, Front/Second	2/3
Front Seat	
Head Room	1013 (39.9)
Legroom	1025 (40.3)
Shoulder Room	1491 (58.7)
Hip Room	1449 (57.0)
Seat Travel	280 (11.0)
Volume, L (cu. ft.)	1546 (54.6)
Rear Seat	
Head Room	995 (39.2)
Legroom	981 (38.6)
Shoulder Room	1474 (58.0)
Hip Room	1428 (56.2)
Knee Clearance	110 (4.3)
Couple	880 (34.6)
Volume, L (cu. ft.)	1438 (50.8)



Jeep® GRAND CHEROKEE SRT8

Canadian Specifications

Cargo Volume

Behind Rear Seat, L (cu. ft.)	994 (35.1)
Rear Seats Folded, L (cu. ft.)	1945 (68.7)

	MODEL	ENGINE	GVWR ^(a) kg (lb.)	CURB WEIGHT ^(b) kg (lb.)	PAYLOAD ^(c) kg (lb.)
4WD	SRT8	6.4-litre	2948 (6500)	2336 (5150)	612 (1350)

(a) Gross Vehicle Weight Rating.

(b) Curb weight includes standard equipment and full quantities of fuel, lubricant and coolant.

(c) Payload is the maximum allowable weight of driver, passengers, cargo, and options, rounded to the nearest 5kg (10 lb).

WEIGHT DISTRIBUTION, F/R

4WD	54/46
------------	-------

BODY

Layout	Longitudinal front engine, transfer case with on demand four-wheel drive
Construction	Steel uniframe

EXHAUST

Type	Dual exhaust with active valves and dual 4-in. (102mm) oval black chrome tips
------	---

SUSPENSION

Front	Short- and long-arm independent (SLA), coil springs, Bilstein Adaptive Damping Suspension (ADS), upper- and lower-control arms ("A" arms), stabilizer bar
Rear	Multi-link rear suspension, coil spring, Bilstein Adaptive Damping Suspension (ADS), aluminum lower control arm, independent upper links (tension and camber) plus a separate toe link, stabilizer bar

STEERING ^(a)

Type	SRT-tuned power rack and pinion
Steering Ratio	17.5:1
Turn Circle, m (ft.)	11.3 (37.1)
Lock-to-Lock Steering Wheel Rotations	3.369

(a) Turning diameter is measured at the outside of the tires at curb height.

Turning diameters and steering wheel turns, lock-to-lock, may differ with optional tires and wheels.



Jeep® GRAND CHEROKEE SRT8

Canadian Specifications

BRAKES

Front

Size and Type, in. (mm)	15.0 x 1.34 (380 x 34) vented disc with Brembo six-piston caliper and ABS
Swept Area, sq. cm (sq. in.)	672 (104.2)

Rear

Size and Type, in. (mm)	13.78 x 1.10 (350 x 28) disc with Brembo four-piston caliper and single-channel ABS
Swept Area, sq. cm (sq. in.)	508 (79.0)
Power Assist	Single-rate, tandem diaphragm vacuum

TIRES

Standard

Size and Type	P295/45ZR20
Mfr. and Model	Pirelli Scorpion Verde – All-Season Performance (run flat)
Revs per km (mile)	1125 (699)

Optional

Size and Type	P295/45ZR20
Mfr. and Model	Pirelli P-Zero – Three Season (run flat)
Revs per km (mile)	1125 (699)

WHEELS

Availability	Standard on Grand Cherokee SRT8
Type and Material	Split five-spoke forged aluminum
Size (in.)	20 x 10

TRAILER TOWING^(a)

	ENGINE	AXLE RATIO	MAXIMUM TRAILER WEIGHT ^(b) kg (LB.)
4WD	6.4-litre V8	3.70	2269 (5000)

(a) For towing heavier trailers up to the Maximum Trailer Weight Ratings shown in the Trailer Towing chart, the vehicle must be equipped with the Trailer Tow Group Class IV for the 6.4-litre engine for North America.

(b) Maximum Trailer Weight = GCWR - Curb Wt. with hitch – 136 kg (300 lb.) (allowance for driver and passenger) and must be decreased by the weight of optional equipment, cargo and additional passengers. Maximum trailer weights shown are rounded to the nearest 23 kg (50 lb.) Tongue weight should be 10-15% of loaded trailer weight but may not cause vehicle to exceed GVWR or GAWR. Load equalizing hitch recommended for trailers over 907 kilograms (2000 lb.)

• • •