

CHRYSLER



200

CANADIAN SPECIFICATIONS

## 2014 Chrysler 200 CANADIAN SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.  
All dimensions are in millimetres (inches) unless otherwise noted.  
All dimensions measured at curb weight with standard tires and wheels.*

### GENERAL INFORMATION

Body Style	Four-door sedan
Assembly Plant	Sterling Heights Assembly, Michigan (U.S.A.)
Vehicle Class	Mid-size sedan
Introduction Date	December 2010

### BODY/CHASSIS

Layout	Transverse front engine with front-wheel drive
Construction	Steel unibody

### ENGINE: 2.4-LITRE, GASOLINE, DOHC, 16-VALVE, VVT, SMPI I-4

Availability	Standard on 200 LX, Touring, Limited models
Type and Description	Four-cylinder inline, tuned intake manifold with electronic active charge motion control valves with dual counter-rotating balance shafts
Displacement	2,360 cu. cm (144 cu. in.)
Bore x Stroke	88 x 97 (3.46 x 3.82)
Valve System	Chain-driven DOHC, 16 valves, electronically controlled dual variable-valve timing (VVT), direct-acting shimless mechanical bucket tappets
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	High-pressure die-cast aluminum block with dry iron liners, cast-aluminum cylinder heads, cast-aluminum ladder frame, forged-steel crankshaft
Compression	10.5:1
Power	173 bhp @ 6,000 rpm
Torque	166 lb.-ft. @ 4,400 rpm
Max. Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	4.23 litres (4.5 qt.)
Coolant Capacity	6.8 litres (7.2 qt.)
Emission Controls	Single catalytic converter dual heated oxygen sensors and engine features



2013 EnerGuide Fuel Economy L/100 km (mpg) City/Hwy	10.0 (28)/6.9 (41) with 4-speed automatic 10.6 (27)/6.5 (43) with 6-speed automatic
---	--

**ENGINE: 3.6-LITRE, GASOLINE, DOHC, 24-VALVE, SMPI V-6**

Availability	Available on 200 Touring, Limited and S models
Type and Description	60-degree bank angle, liquid-cooled, three-plenum intake manifold with electronically controlled manifold tuning valve and short-runner valves
Displacement	3605 cu. cm (220 cu. in.)
Bore x Stroke	96 x 83 mm (3.78 x 3.28)
Valve System	DOHC, 24 valves, hydraulic, roller finger followers
Fuel Injection	Sequential, multiport, electronic
Construction	High-pressure die-cast A380 aluminum block with iron liners and semi-permanent mould A319 aluminum heads
Compression Ratio	10.2:1
Power	283 bhp @ 6,400 rpm
Torque	260 lb.-ft. @ 4,400 rpm
Max. Engine Speed	6,800 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	5.7 litres (6 qt.) with dry filter
Coolant Capacity	9.75 litres (10.3 qt.)
Emission Controls	Dual catalytic converters, four heated oxygen sensors, electronic EGR, and internal engine features
2013 EnerGuide Fuel Economy L/100km (mpg) City/Hwy	11 (26)/6.8(42)

**TRANSAXLE: 40TES, AUTOMATIC FOUR-SPEED OVERDRIVE**

Availability	Standard on 200 LX and touring model
Description	Four-speed overdrive, adaptive electronic control, electronically modulated converter clutch
Gear Ratios	
1st	2.842
2nd	1.57
3rd	1.00
4th	0.69
Reverse	2.21



Final Drive Ratio	3.91 with 2.4-liter engine
Overall Top Gear	2.69 with 2.4-liter engine

**TRANSAXLE: 62TE, AUTOMATIC SIX-SPEED OVERDRIVE**

Availability	Standard on 200 Limited and S models; Available on LX and Touring models
Description	Six-speed, adaptive electronic control or Auto Stick driver-interactive manual control and electronically modulated torque converter clutch
<b>Gear Ratios</b>	
1st	4.127
2nd	2.842
3rd	2.283
4th	1.452
5th	1
6th	0.69
Reverse	3.214
Transfer Ratio	0.95
Final Drive Ratio	3.16 with 3.6-litre engine, 3.43 with 2.4-litre engine
Overall Top Gear	2.06 with 3.6-litre engine, 2.24 with 2.4-litre engine

**SUSPENSION**

Front	Independent MacPherson strut, coil spring over gas-charged shock absorbers, stabilizer bar
Rear	Multi-link independent with coil springs, link-type stabilizer bar, gas-charged shock absorbers and isolated rear suspension cradle

**STEERING**

Type	Power rack and pinion
Overall Ratio	16.65:1
Turning Diameter (curb-to-curb)	11.1 m (36.5 ft.) (17-in. wheels), 11.5 m (37.7 ft.) (18-in. wheels)
Steering Turns (lock-to-lock)	2.98 (17-in. wheels), 2.89 (18-in. wheels)



**BRAKES mm (in.) unless otherwise noted**

Power-assist Type	204 x 230 (8 x 9) tandem-diaphragm vacuum
Availability	Standard on LX, Touring, Limited and S models
Front	
Size and Type	294 x 26 (11.5 x 1.0) vented rotors with 57.0 (2.2) single-piston floating caliper
Swept Area (Total Front)	1,442.1 sq. cm (223.5 sq. in.)
Rear	
Size and Type	262 x 10 (10.3 x 0.4) solid rotor with 35.0 (1.4) single-piston floating caliper
Swept Area (Total Rear)	894.6 sq. cm (138.6 sq. in.)
Parking Brake Type	Drum-in-hat
Anti-lock Brake System (ABS)	Standard
Electronic Stability Control (ESC)	Standard
Traction Control	Standard
Brake Assist	Standard

**DIMENSIONS AND CAPACITIES mm (in.) unless otherwise noted**

Wheelbase	2,765 (108.9)
Track, Front	1,567 (61.7)
Track, Rear	1,594 (62.7)
Overall Length	4,870 (191.7)
Overall Width	1,843 (72.5) without side mirrors / 2,121 (83.5) with side mirrors
Overall Height	1,482 (58.4) (For P225/55R17)
Aero	
Cd	0.34
Fuel Tank Capacity	64.0 litre (14.1 gal.) standard and FFV 18.5 PZEV
Towing Capabilities, NAFTA Markets kg (lb.) <sup>(a)</sup>	
2.4-litre Automatic Transmission	450 (1,000)
3.6-litre Automatic Transmission	450 (1,000)
<small>(a) Maximum frontal area of trailer or boat: 2.04 square metre (22 square feet) 3.6L engine and 1.02 square metre (11 square feet) 2.4L engine.</small>	
Curb Weight, Base Vehicle, kg (lb.)	
2.4-litre Gasoline Engine	200 Touring — 1,544 (3,402.8)
3.6-litre Gasoline Engine	200 Touring — 1,622 (3,575.8)



**ACCOMMODATIONS mm (in.) unless otherwise noted**

Seating Capacity - F/R	2/3
Total Interior Passenger Volume	2,840 litres (100.3 cu. ft.)
Front	
Head Room w/o Sunroof	1,017 (40.1)
Head Room w/Sunroof	963 (37.9)
Legroom	1,077 (42.4)
Shoulder Room	1,431 (56.3)
Hip Room	1,336 (52.6)
Seat Travel	260 (10.2)
Front Compartment Volume	1,566 litres (55.3 cu. ft.)
Rear	
Head Room	975 (38.4)
Legroom	919 (36.2)
Shoulder Room	1,422 (56.0)
Hip Room	1,341 (52.8)
Knee Clearance	50 (2.0)
Rear Compartment Volume	1,274 litres (45.0 cu. ft.)
Cargo	
Trunk Lift-over Height	799 (31.5) (For P225/55R17)
Luggage Compartment Volume	385 litres (13.6 cu. ft.)

**WHEELS (in.)**

Availability	Standard on 200 LX model
Type and Material	Steel with Sparkle Silver wheel cover
Size	17 in. x 6.5 in.
Availability	Standard on 200 Touring model, available on LX model
Type and Material	Machined cast-aluminum, Sparkle Silver
Size	17 in. x 6.5 in.
Availability	Standard on 200 Limited model, available on Touring model
Type and Material	Polished aluminum
Size	18 x 7.0 in.

CHRYSLER



200

CANADIAN SPECIFICATIONS

Availability	Standard on 200 S model
Type and Material	Polished Aluminum with Black Painted Pockets
Size	18 x 7.0 in.

Availability	Available on Touring model
Type and Material	Cast Aluminum, Satin Silver
Size	18 x 7.0 in.

**TIRES**

Availability	Available on 200 LX
Size and Type	P225/55R17, All-season
Model	Michelin Primacy MXV4 Touring
Revs per km (mile)	483 (778)

Availability	Available on 200 Limited model, optional on Touring model
Size and Type	P225/50R18, All-season Touring
Model	Goodyear Eagle LS-2 Touring
Revs per km (mile)	483 (777)

Availability	Standard on 200 LX and Touring models
Size and Type	225/55R17, All-season
Model	Nexen CP671
Revs per km (mile)	484 (779)

