# 2015 Fiat 500L **CANADIAN SPECIFICATIONS**

Specifications are based on the latest product information available at the time of publication. All dimensions are in millimetres (inches) unless otherwise noted. All dimensions measured at curb weight with standard tires and wheels.

#### **GENERAL INFORMATION**

Vehicle Type	B-segment multipurpose vehicle (MPV)	
EnerGuide Vehicle Class	Station Wagon - Small	
Assembly Plant	Kragujevac (Serbia)	
Introduction Date	Mid-2013 as a 2014 model	

#### **BODY/CHASSIS**

Layout	Transverse-mounted front engine, front-wheel drive
Construction	Unitized steel body

#### ENGINE: 1.4-LITRE SOHC 16-VALVE TURBOCHARGED MULTIAIR® INLINE FOUR-CYLINDER

Availability	Standard on all 500L models		
Type and Description	Inline four-cylinder, liquid-cooled, turbocharged		
Displacement	1,368 cu. cm (83.48 cu. in.)		
Bore x Stroke	72.0 x 84.0 (2.83 x 3.31)		
Valve System	Belt-driven, MultiAir, SOHC, 16 valves, hydraulic end-pivot roller rockers		
Fuel Injection	Sequential, multiport, electronic, returnless		
Construction	Cast-iron block with aluminum-alloy head and aluminum-alloy bedplate		
Compression Ratio	9.8:1		
Maximum Turbo Boost	21 psi / 1.45 bar		
Power	160 hp @ 5,500 rpm (114 hp/litre)		
Torque	184 lbft. @ 2,500-4,000 rpm		
Max. Engine Speed	6,500 rpm (electronically limited)		
Fuel Requirement	87 octane (R+M)/2 acceptable		
	91 octane recommended		
Oil Capacity	3.8 litres (4.0 qt.) with dry filter		
Coolant Capacity	4.4 litres (4.6 qt.)		
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors and internal engine features		
Max. Gross Trailer Weight	Not rated for trailer tow		

EnerGuide 5-cycle Fuel Economy L/100km (mpg) City/Hwy*	9.3 (30) / 7.2 (39) (six-speed manual transmission) 10.0 (28) / 7.2 (39) (Euro Twin Clutch six-speed automatic transmission) N/A (6-speed heavy-duty automatic transmission)
Engine Assembly Plant	Termoli (Italy)

<sup>\*</sup>Based on 2014 EnerGuide fuel consumption ratings. New 5-cycle test method shown.

### **C635 SIX-SPEED MANUAL TRANSMISSION**

Availability	Standard on all 500L models		
Description	1st, 2nd gear: Double Cone		
	3rd, 4th, 5th, 6th gear: Single Cone		
Gear Ratios			
1st	4.154		
2nd	2.118		
3rd	1.361		
4th	0.978		
5th	0.756		
6th	0.622		
Reverse	4.00		
Final-drive Ratio	3.833		
Overall Top Gear	2.38		

### C635 EURO TWIN CLUTCH SIX-SPEED TRANSMISSION

Availability	Optional on 500L Pop	
Description	1st, 2nd gear: Double Cone 3rd, 4th, 5th, 6th gear: Single Cone	
Gear Ratios		
1st	4.154	
2nd	2.269	
3rd	1.435	
4th	0.978	
5th	0.755	
6th	0.622	
Reverse	4.00	
Final-drive Ratio	4.118	
Overall Top Gear	2.56	

# AISIN SIX-SPEED AUTOMATIC TRANSMISSION

Availability	Optional on 500L Sport, Trekking and Lounge	
Gear Ratios		
1st	4.04	
2nd	2.37	
3rd	1.56	
4th	1.16	
5th	0.85	
6th	0.67	
Reverse	3.19	
Final-drive Ratio	3.683	
Overall Top Gear	2.47	

### **BRAKES**

Availability	Standard on all 500L models		
Front			
Rotor size and type	305 x 28 (12.0 x 1.10) vented		
Caliper size and type	57 (2.24) single-piston with cast iron		
Swept area	876.1 sq. cm (345 sq. in.)		
Rear			
Rotor size and type	264 x 10 (10.4 x 0.4) solid		
Caliper size and type	38 (1.49) single-piston with aluminum housing		
Swept area	591.8 sq. cm (233 sq. in.)	591.8 sq. cm (233 sq. in.)	

# DIMENSIONS AND CAPACITIES(a) mm (in.) unless otherwise noted

Wheelbase	2,611 (102.8)	
Track, Front	1,501 (59.1)	
Track, Rear	1,510 (59.4)	
Overall Length	4,249 (167.3)	
Overall Width	1,773 (69.8) — without mirrors	
	2,037 (80.2) — with mirrors	
Overall Height	1,669 (65.7)	
Ground Clearance	119 (4.7)	
Drag Coefficient (Cd) (estimated)	0.310 — 500L Pop/Sport/Lounge	
	0.320 — 500L Trekking	

Curb Weight (estimated)	1,453 kg (3,203 lb.) — (six-speed manual) 1,476 kg (3,254 lb.) — (six-speed Euro Twin Clutch automatic) 1,475 kg (3,251 lb.) — (six-speed automatic)	
Weight Distribution, per cent F/R	61/39 — (six-speed manual) 61/39 — (six-speed Euro Twin Clutch automatic) 58/42 — (six-speed automatic)	
Fuel Tank Capacity	50 litres (11 gal.)	

<sup>(</sup>a) All dimensions measured at curb weight with standard tires.

## **ACCOMMODATIONS**

## mm (in.) unless otherwise noted

Seating Capacity, F/R	2/3	
Front Seat		
Head room	1,034 (40.7)	
	1,026 (40.4) with dual-pane sunroof	
Legroom	1,016 (40.0)	
Shoulder room	1,455 (57.3)	
Hip room	1,394 (54.9)	
Total seat travel	211 (8.3) — driver	
	229 (9.0) — passenger	
Front row interior volume	1,529 litres (54.0 cu. ft.)	
Rear Seat		
Head room	983 (38.7)	
	965 (38.0) with dual-pane sunroof	
Legroom	932 (36.7)	
Shoulder room	1,387 (54.6)	
Hip room	1,255 (49.4)	
Total seat travel	119 (4.7)	
Second row interior volume	1,269 litres (44.8 cu. ft.)	
Total Interior Volume	2,798 litres (98.8 cu. ft.)	
Luggage Compartment Volume	603 litres (21.3 cu. ft.)	
Interior Volume Index	3,401 litres (120.1 cu. ft.)	
Trunk Liftover Height	658 (25.9)	

т	1	D	ᆮᄋ
		$\mathbf{r}$	⊏ാ

TINEO	
Availability	Standard on 500L Pop, Sport and Lounge
Size and Type	205/55R16 BSW All-season
Mfr. and Model	Continental Conti ProContact or Goodyear Eagle LS2
Revs per km (mile)	519 (836)
Availability	Standard on 500L Trekking Included with 17-in. wheels on 500L Lounge
Size and Type	225/45R17 BSW All-Season
Mfr. and Model	Continental Conti ProContact or Goodyear Eagle LS2
Revs per km (mile)	517 (832)
WHEELS (in.)	
Availability	Standard on 500L Pop
Type and Material	Steel wheels with grey painted wheel covers
Size	16 x 6.0
Availability	Standard on 500L Sport and Lounge
Type and Material	Cast-aluminum, 13-spoke radial design, fully painted grey
Size	16 x 6.5
Availability	Optional on 500L Sport
Type and Material	Cast-aluminum, seven-spoke, oval-twist design, painted grey with black pockets
Size	16 x 6.5
Availability	Standard on 500L Trekking
Type and Material	Cast-aluminum, seven-hole design, machined face with painted grey pockets
Size	17 x 7.0
Availability	Optional on 500L Trekking and Lounge
Type and Material	Cast-aluminum, five-oval design, painted grey with grey pockets
Size	17 x 7.0

Availability	Optional on 500L Lounge
Type and Material	Cast-aluminum, seven-spoke, dual-twist design, painted grey with black pockets
Size	17 x 7.0
Availability	Optional on 500L Lounge
Availability  Type and Material	Optional on 500L Lounge  Cast-aluminum, seven-spoke, dual-twist design, painted grey with white pockets

