



RAM

Cargo Van

CANADIAN SPECIFICATIONS

2015 Ram C/V (Cargo Van) CANADIAN SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

GENERAL INFORMATION

Vehicle Type	Multipurpose vehicle, front-wheel drive
Assembly Plant	Windsor, Ontario
EnerGuide Vehicle Class	Multipurpose vehicle
Introduction date	August 2011 as a 2012 model year

BODY/CHASSIS

Layout	Transverse front engine, front-wheel drive
Construction	Unitized steel with hinged front doors; sliding left and right side doors — rear liftgate with gas props

ENGINE: 3.6-LITRE, GASOLINE, DOHC, 24-VALVE, V6

Availability	Standard
Type and Description	60-degree bank angle, liquid-cooled, with three-plenum intake manifold, electronically-controlled manifold tuning valve and short-runner valves
Displacement	3,605 cu. cm (220 cu. in.)
Bore x Stroke	96 x 83 (3.78 x 3.27)
Valve System	DOHC, 24 valves, hydraulic, roller finger followers
Fuel Injection	Sequential, multi-port, electronic
Construction	High-pressure die-cast A380 aluminum block with iron liners and semi-permanent mould A319 aluminum heads
Compression Ratio	10.2:1
Power	283 bhp @ 6,400 rpm
Torque	260 lb.-ft. @ 4,400 rpm
Max. Engine Speed	6,800 rpm (electronically limited)
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — preferred Unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	5.88 litres (6 qt.) with dry filter
Coolant Capacity	9.75 litres (10.3 qt.)
Emission Controls	Dual catalytic converter, four heated oxygen sensors, electronic EGR and internal engine features



RAM

Cargo Van

CANADIAN SPECIFICATIONS

EnerGuide 5-Cycle Fuel Economy L/100 km (mpg) City/Hwy*	13.3 (21) / 9.1 (31)*
---	-----------------------

*Based on 2014 EnerGuide fuel consumption ratings for Ram C/V. 5-cycle test method used.

Assembly Plant	Trenton, Michigan (U.S.A.)
----------------	----------------------------

*Based on 2014 Energuide fuel consumption ratings. 5-cycle test method used.

TRANSAXLE: 62TE, AUTOMATIC SIX-SPEED OVERDRIVE

Availability	Standard
--------------	----------

Description	Six-speed, adaptive electronic control, electronically-modulated torque converter clutch, Electronic Range Select (ERS)
-------------	---

Gear Ratios

1st	4.127
2nd	2.842
3rd	2.283
4th	Upshift – 1.452 WOT kickdown – 1.570
5th	1.0
6th	0.690
Reverse	3.214
Transfer Ratio	0.95
Final Drive Ratio	3.16
Overall Top Gear	2.24

ELECTRICAL SYSTEM

Alternator	160 amp
Battery	730 CCA, maintenance-free

SUSPENSION

Front	Independent MacPherson strut, coil over gas-charged shock absorbers, stabilizer bar with isolated suspension cradle
Rear	Twist-beam axle with coil springs, track bar

STEERING

Type	Power rack and pinion
Overall Ratio	14.3:1
Turning Diameter (curb-to-curb)	11.92 m (39.1 ft.)
Steering Turns (lock-to-lock)	2.90



RAM

Cargo Van

CANADIAN SPECIFICATIONS

BRAKES

mm (in.) unless otherwise noted

Power Assist Type	All — 230 x 230 (9 x 9) tandem-diaphragm vacuum — standard
Power Assist Type	All — 204 x 230 (8 x 9) tandem-diaphragm vacuum — optional
Availability	Standard on all models
Front	
Size and Type	330 x 28 (13.0 x 1.1) vented rotors with 51 mm single-piston caliper — standard
Swept Area (total front)	475 sq. cm (73.6 sq. in.) — standard
Size and Type	302 x 28 (11.9 x 1.1) vented rotors with 66 mm single-piston caliper — optional
Swept Area (total front)	350 sq. cm (54.3 sq. in.) — optional
Rear	
Size and Type	328 x 12 (12.9 x 0.47) solid rotors with 45 mm single-piston IPB caliper — standard
Swept Area (total rear)	429 sq. cm (66.5 sq. in.) — standard
Size and Type	305 x 12 (12.0 x 0.47) solid rotors with 42 mm single-piston IPB caliper - Optional
Swept Area (total rear)	350 sq. cm (54.3 sq. in.) — optional
Parking Brake Type	Integral parking brake
Four-wheel Anti-lock brakes	Standard
Electronic Stability Control	Standard
All-speed traction control	Standard

DIMENSIONS AND CAPACITIES

mm (in.) unless otherwise noted

Wheelbase	3,078 (121.2)
Overhang — Front	960 (37.8)
Overhang — Rear	1,113 (43.8)
Track — Front	1,664 (65.5)
Track — Rear	1,646 (64.8)
Overall Length	5,151 (202.8)
Overall Width	1,999 (78.7)
Overall Width with Mirrors	2,273 (89.5)
Overall Height	1,753 (69.0)
Liftover Height	665 (26.2)
Cargo Width at Wheelhouse	1,237 (48.7)



RAM

Cargo Van CANADIAN SPECIFICATIONS

Maximum Cargo Height	1,224 (48.2)
Angle of Approach (curb load) (degrees)	13.9
Angle of Departure (curb load) (degrees)	20.6
Breakover Angle (curb load) (degrees)	14.2
Minimum Running Ground Clearance (curb load)	163 (6.4)
Fuel Tank Capacity	76 litres (17 gal.)
Gross Vehicle Weight Rating (GVWR)	2,744 kg (6,050 lb.)
Towing Capacity	1,633 kg (3,600 lb.)
Curb Weight	1,882 kg (4,150 lb.)
Payload	816 kg (1,800 lb.)
Weight Distribution % F/R	59/41

ACCOMMODATIONS

mm (in.) unless otherwise noted

Seating Capacity — F//R	2
-------------------------	---

Front

Head Room	1,011 (39.8)
Head Room with Sunroof	945 (37.2)
Legroom	1,034 (40.7)
Shoulder Room	1,618 (63.7)
Hip Room	1,483 (58.4)
Seat Travel	221 (8.7)

Cargo Volume

Maximum Cargo Volume	4,403 litres (155.5 cu. ft.)
Total Passenger plus Cargo Volume	5,544 litres (195.8 cu. ft.)

WHEELS (in.)

Availability	Standard
Type and Material	Painted steel with bolt-on wheel cover
Size	17 x 6.5



RAM

Cargo Van

CANADIAN SPECIFICATIONS

TIRES

Availability	Standard
Size and Type	225/65R17 BSW, All-season
Model	Yokohama Avid S33
Revs per km (mile)	456 (728)

