

**RAM****ProMaster City**
CANADIAN SPECIFICATIONS

2015 Ram ProMaster City CANADIAN SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

GENERAL INFORMATION

Body Styles	ProMaster City Cargo Van ProMaster City Wagon
Wheelbase	2,855 (122.4)
Assembly Plant	Bursa (Turkey)

ENGINE: 2.4-LITRE 24-VALVE DOHC I-4

Description	Inline four-cylinder, 16-valve MultiAir2 with multiport fuel injection
Displacement	2,360 cu. cm (144 cu. in.)
Bore x Stroke	88mm x 97mm
Valve System	SOHC, four valves per cylinder (16 total)
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	10:1
Power	178 hp @ 6,400 rpm
Torque	174 lb.-ft. @ 3,900 rpm
Max. Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane
Oil Capacity	5.2 litres (5.5 qt.)
Coolant Capacity	6.7 litres (7.1 qt.)
Emission Controls	Single catalytic converter, heated wide band lambda sensor upstream and mid-catalyst heated oxygen sensor



RAM

ProMaster City
CANADIAN SPECIFICATIONS

TRANSMISSION: 948TE NINE-SPEED AUTOMATIC

Description	Planetary gear train, transverse layout
Availability	Standard on all models
Ratio Spread	9.79
Gear Ratios	
1st	4.70
2nd	2.84
3rd	1.90
4th	1.38
5th	1.00
6th	0.80
7th	0.69
8th	0.58
9th	0.47
Axle	3.73

ELECTRICAL SYSTEM

Alternator	160-amp
Battery	95 amp with 700 CCA

BODY AND CHASSIS

Layout	Transverse front engine
Construction	Unibody

