

## 2016 Chrysler 200 CANADIAN SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.  
All dimensions are in millimetres (inches) unless otherwise noted.  
All dimensions measured at curb weight with standard tires and wheels.*

### GENERAL INFORMATION

Body Style	Four-door sedan
Assembly Plant	Sterling Heights, Michigan (U.S.A.)
EnerGuide Vehicle Class	Mid-size sedan

### BODY AND CHASSIS

Layout	Transverse front engine with front-wheel drive (FWD) or all-wheel drive (AWD)
Construction	Steel uni-frame

### ENGINE: 2.4-LITRE MULTIAIR2 TIGERSHARK, I-4 WITH ENGINE

Availability	Standard — all models
Type and Description	Four-cylinder inline, 16-valve MultiAir2 with multiport fuel injection
Displacement	2,360 cu. cm (144 cu. in.)
Bore x Stroke	88 x 97 (3.46 x 3.82)
Valve System	SOHC, 16 valves (4 valves per cylinder)
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	High-pressure die-cast aluminum block with dry iron liners, cast-aluminum cylinder heads, cast-aluminum ladder frame, forged-steel crankshaft
Compression	10.0:1
Power	184 hp @ 6,250 rpm (preliminary)
Torque	173 lb.-ft. @ 4,600 rpm (preliminary)
Max. Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane
Oil Capacity	5.2 litres (5.5 qt.)
Coolant Capacity	7.1 litres (7.5 qt.)
Emission Controls	GPEC3 engine-management system with close-coupled catalyst; and wide range O <sup>2</sup> sensor (a)
Engine Assembly Plant	Dundee, Michigan (U.S.A.)
2015 EnerGuide Fuel Economy L/100km (mpg) city/hwy	10.2 (28) / 6.4 (44)

## ENGINE: 3.6-LITRE PENTASTAR™ V6

Availability	Optional — Limited, 200S and 200C models
Type and Description	60-degree bank angle, liquid-cooled, three-plenum intake manifold with electronically-controlled manifold tuning valve and short-runner valves
Displacement	3,605 cu. cm (220 cu. in.)
Bore x Stroke	96 x 83 mm (3.78 x 3.27)
Valve System	Chain-drive DOHC, 24 valves (4 valves per cylinder), hydraulic end-pilot roller rockers, variable cam phasing on intake and exhaust cams
Fuel Injection	Sequential, multiport, electronic
Construction	High-pressure die-cast A380 aluminum block with iron liners and semi-permanent mould A319 aluminum heads
Compression Ratio	10.2:1
Power	295 bhp @ 6,350 rpm
Torque	262 lb.-ft. @ 4,250 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	5.7 litres (6 qt.) with dry filter SAE 5W30
Coolant Capacity	8.12 litres (8.58 qt.)
Emission Controls	Integrated cast-aluminum header manifolds; positive crankcase ventilation; inlet and exhaust cam phasers with internal exhaust gas recirculation (no EGR/AIR required); evaporative emissions system
2015 EnerGuide Fuel Economy L/100km (mpg) city/hwy	FWD 12.4 (23) / 7.5 (38) AWD 12.8 (22) / 8.1 (35)
Engine Assembly Plant	Trenton, Michigan (U.S.A.)

## TRANSMISSION: 948TE/9HP48, AUTOMATIC NINE-SPEED

Availability	Standard — all models
Description	Nine-speed FWD/AWD, electronically-controlled automatic overdrive transmission with torque converter clutch. Clutch-to-clutch architecture, with integral electro/hydraulic controls module
Gear Ratios	
1st	4.71
2 <sup>nd</sup>	2.84
3 <sup>rd</sup>	1.91
4 <sup>th</sup>	1.38
5 <sup>th</sup>	1.00
6 <sup>th</sup>	0.81
7 <sup>th</sup>	0.70

8 <sup>th</sup>	0.58
9 <sup>th</sup>	0.48
Reverse	3.81
Spread	9.81
Final Drive Ratio – 948TE	3.73 with 2.4-litre engine
Final Drive Ratio – 9HP48	4.08 with 3.6-litre engine

## ELECTRICAL SYSTEM

Alternator	160-amp
Battery	600-amp maintenance-free (LX, Limited) 730-amp (200S, 200C)

## SUSPENSION

Front	MacPherson strut, dual reacting twin tube shock absorbers
Rear	Multi-link independent dual reacting twin tube shock absorbers

## STEERING

Type	Electric power rack and pinion
Overall Ratio	15:2 (FWD and AWD)
Turning Diameter (curb-to-curb)	FWD/AWD 12.13 m (39.8 ft.)
Steering Turns (lock-to-lock)	2.67

## BRAKES

### mm (in.) unless otherwise noted

Power-assist Type	Vacuum assist
Availability	Standard on Touring and Limited models
<b>Front</b>	
Size and Type	2.4-litre: (305 x 28) rotors with (60.0) single-piston floating caliper 3.6-litre: (330 x 28) rotors with (60.0) single-piston floating caliper
Swept Area (Total Front)	2.4-litre: 820.08 sq. cm (127.11 sq. in.) 3.6-litre: 901.76 sq. cm (139.77 sq. in.)
<b>Rear</b>	
Size and Type	(278 x 12) rotors with (38.0) single-piston aluminum caliper
Swept Area (Total Rear)	638.6 sq. cm (98.98 sq. in.)
Parking Brake Type	Electronic park brake
Anti-lock Brake System (ABS)	Standard

Electronic Stability Control (ESC)	Standard
Traction Control	Standard
Brake Assist	Standard

**DIMENSIONS AND CAPACITIES**  
mm (in.) unless otherwise noted

Wheelbase	2,742 (108.0)
Track, Front	1,578 (62.1)
Track, Rear	1,576 (62.0)
Overall Length	4,885 (192.3)
Overall Width	1,871 (73.6)
Overall Height	1,491 (58.7)
Front Overhang	1,039 (40.9)
Rear Overhang	1,103 (43.4)
Approach Angle (Deg.)	13.5
Departure Angle (Deg.)	17.8
Ground Clearance	3.6-litre FWD with 17-in. tire (lowest available): 147mm
Aero	
Cd	0.27
Fuel Tank Capacity	FWD and AWD: 59.8 litres (13.1 gal.)
Towing Capabilities, NAFTA kg (lb.)	No trailer tow recommended
Curb Weight, Base Vehicle	1,575 kg (3,473 lb.)
GVWR (Base vehicle)	2,092 kg (4,612 lb.)

**ACCOMMODATIONS**  
mm (in.) unless otherwise noted

Seating Capacity - F/R	2/3
Total Interior Passenger Volume	2,871 litres (101.4 cu.ft.)
Front	
Headroom	983 (38.7)
Legroom	1,071 (42.2)
Shoulder Room	1,485 (58.5)
Hip Room	1,384 (54.5)
Seat Travel	210 (8.3)
Front Compartment Volume	1,566 litres (55.3 cu.ft.)



## 2016 CHRYSLER 200 CANADIAN SPECIFICATIONS

### Rear

Headroom	950 (37.4)
Legroom	956 (37.6)
Shoulder Room	1,441 (56.7)
Hip Room	1,338 (52.7)
Knee Clearance	71.3 (2.8)
Rear Compartment Volume Index,	1,305 litres (46.1 cu. ft.)

### Cargo

Trunk Lift-over Height	726 (28.6 cu. ft.)
Trunk Volume	453 litres (16 cu. ft.)
Interior Volume	3,324 litres (117.4 cu. ft.)
Passenger Volume	2,871 litres (101.4 cu. ft.)

### WHEELS (in.)

Availability	200 LX
Type and Material	Steel with cover
Size	17 in. x 7.0

Availability	200 Limited
Type and Material	Cast Aluminum, Painted Tech Silver Cast Aluminum, Painted Satin Silver
Size	17 in. x 7.5 18 in. x 8.0

Availability	200S
Type and Material	Cast Aluminum, Painted Satin Carbon Cast Aluminum, Painted Hyper Black
Size	18 in. x 8.0 19 in. x 8.0

Availability	200C
Type and Material	Cast Aluminum, Painted Satin Silver Cast Aluminum, Polished Satin Clear Cast Aluminum, Polished face, painted pockets
Size	17 in. x 7.5 18 in. x 8.0 19 in. x 8.0

## TIRES

Availability	200 LX
Size and Type (Revs per km)	Bridgestone 215/55R17 (489) Nexen 215/55R17 (493) Goodyear 215/55R17 (491)
Availability	200 Limited
Size and Type (Revs per km)	Bridgestone 215/55R17 (489) Nexen 215/55R17 (493) Goodyear 215/55R17 (491) Nexen 235/45R18 (492)
Availability	200S
Size and Type (Revs per km)	Bridgestone 235/45R18 (495) Nexen 235/40R19 (490)
Availability	200C
Size and Type (Revs per km)	Bridgestone 215/55R17 (489) Goodyear 215/55R17 (491) Bridgestone 235/45R18 (495) Nexen 235/40R19 (490)

