



2016 RAM 1500 CANADIAN SPECIFICATIONS

2016 Ram 1500 CANADIAN SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

GENERAL INFORMATION

Vehicle Type	Regular Cab, Quad Cab, and Crew Cab, 2WD, 4WD
Assembly Plant	Regular Cab: Saltillo (Mexico) Quad Cab: Warren, Michigan (U.S.A.) Crew Cab: Warren, Michigan (U.S.A.) and Saltillo (Mexico)
EnerGuide Vehicle Class	Standard Pickup

BODY/CHASSIS

Layout	2WD — Longitudinal, front engine 4WD — Longitudinal, front engine, transfer case
Construction	2WD — Ladder-type frame, steel cab, double-wall steel pickup box 4WD — Ladder-type frame, steel cab, double-wall steel pickup box

ENGINE: 3.6-LITRE PENTASTAR™ V6

Type and Description	60-degree V-type, liquid-cooled
Displacement	3,604 cu. cm (220 cu. in.)
Bore x Stroke	96.0 x 83.0 (3.78 x 3.27)
Valve System	Chain-driven DOHC, 24 valves and hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	10.2:1
Power	305 hp at 6,400 rpm
Torque	269 lb.-ft. at 4,175 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2, E85-compatible
Oil Capacity	5.7 litres (6.0 qt.)
Coolant Capacity	13.25 litres (14.0 qt.)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors
2015 EnerGuide Fuel Economy L/100 km (mpg) city/hwy	12.9 (22) / 9.3 (30) — 4x2 models 14.6 (19) / 10.1 (28) — 4x4 models



2016 RAM 1500 CANADIAN SPECIFICATIONS

ENGINE: 3.0-LITRE ECODIESEL V6

Type and Description	60-degree V-type, liquid-cooled
Displacement	2,988 cu. cm (182 cu. in.)
Bore x Stroke	83 x 92 (3.27 x 3.60)
Valve System	Chain-driven DOHC, 24 valves
Fuel Injection	Common-rail, 2000 bar, Solenoid Injectors
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	16.5:1
Power	240 hp at 3,600 rpm
Torque	420 lb.-ft. at 2,000 rpm
Max. Engine Speed	4,800 rpm (electronically limited)
Fuel Requirement	Ultra Low-sulfur diesel
Oil Capacity	7.8 litres (10.5 qt.)
Coolant Capacity	11.4 litres (12 qt.)
Emission Controls	Cooled EGR, oxidation catalyst, diesel particulate filter, SCR w/urea injection
2015 EnerGuide Fuel Economy L/100 km (mpg) city/hwy	11.3 (25) / 8.0 (35) — 4x2 models 12.1 (23) / 8.8 (32) — 4x4 models

ENGINE: 5.7-LITRE HEMI® V8

Type and Description	90-degree V8, liquid-cooled
Displacement	5,654 cu. cm (345 cu. in.)
Bore x Stroke	99.5 x 90.9 (3.92 x 3.58)
Valve System	Variable-cam timing, pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
Power	395 hp @ 5,600 rpm
Torque	410 lb.-ft. @ 3,950 rpm
Max. Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — recommended Unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	6.6 litres (7.0 qts.)
Coolant Capacity	13.33 litres (14.0 qts)
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features



2016 RAM 1500 CANADIAN SPECIFICATIONS

2015 EnerGuide Fuel Economy L/100 km (mpg city/hwy eight-speed automatic)	15.7 (18) / 10.9 (26) — 4x2 models
---	------------------------------------

16.2 (17) / 11.5 (25) — 4x4 models

2015 EnerGuide Fuel Economy L/100 km (mpg city/hwy six-speed automatic)	17.1 (17) / 12.0 (24) — 4x2 models
---	------------------------------------

17.7 (16) / 12.7 (22) — 4x4 models

TRANSMISSION: 65RFE AUTOMATIC SIX-SPEED

Availability	Available with 5.7-litre HEMI V8 equipped trucks
--------------	--

Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
-------------	--

Gear Ratios

1st	3.00
-----	------

2nd	1.67
-----	------

3rd	1.50
-----	------

4th	1.00
-----	------

5th	0.75
-----	------

6th	0.67
-----	------

Reverse	3.00
---------	------

Axle Gear Ratios	3.21, 3.55, 3.92
------------------	------------------

TRANSMISSION: TORQUEFLITE 845RE EIGHT-SPEED AUTOMATIC

Availability	Standard with 3.6-litre Pentastar V6
--------------	--------------------------------------

Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
-------------	---

Gear Ratios

1st	4.71
-----	------

2nd	3.14
-----	------

3rd	2.10
-----	------

4th	1.67
-----	------

5th	1.29
-----	------

6th	1.00
-----	------

7th	0.84
-----	------

8th	0.67
-----	------

Reverse	3.30
---------	------

Axle Gear Ratios	3.21, 3.55, 3.92 (Rebel only)
------------------	-------------------------------



2016 RAM 1500 CANADIAN SPECIFICATIONS

TRANSMISSION: ZF TORQUEFLITE 8HP70 EIGHT-SPEED AUTOMATIC

Availability	Standard with 3.0-litre EcoDiesel V6 and select 5.7-litre HEMI V8 equipped trucks
Description	Adaptive electronic control, automatic or ERS manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Gear Ratios	3.21 (excluding 3.0-litre EcoDiesel V6), 3.55 (excluding 5.7-litre HEMI V8), 3.92 (3.6-litre Pentastar V6 Rebel only)

TRANSFER CASE: BW 44-45 PART-TIME

Availability	3.0-litre EcoDiesel V6 4x4, 3.6-litre Pentastar V6 4x4, and 5.7-litre HEMI V8 4x4 (all Powertrains)
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Centre Differential Type	None

TRANSFER CASE: BW 44-44 ON-DEMAND

Availability	3.0-litre EcoDiesel V6 4x4, 3.6-litre Pentastar V6 4x4, and 5.7-litre HEMI V8 4x4 (All Powertrains)
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD Auto; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Centre Differential Type	None



2016 RAM 1500 CANADIAN SPECIFICATIONS

AXLES

Front	ZF 215 mm
Rear	C235 mm (available limited slip)
Available Ratios	3.21, 3.55, 3.92

ELECTRICAL SYSTEM

Architecture	Powernet
Alternator	160-amp, 180-amp, 220-amp (Stop-start system and Special Services Package) 230-amp (3.0-litre EcoDiesel V6)
Battery	Group 65, low-maintenance 730 CCA (Stop-start features 800 CCA absorbed glass mat)

SUSPENSION

Front	Upper and lower "A" arms, coil springs, twin-tube shock absorbers, stabilizer bar. Optional air suspension replaces twin-tube shock absorbers and coil springs. Rebel features Bilstein monotube shocks with air suspension
Rear	Five-link with track bar, coil springs, stabilizer bar, twin-tube shock absorbers, solid axle. Optional air suspension replaces twin-tube shock absorbers and coil springs. Rebel features Bilstein monotube shocks with air suspension

BRAKES

Front	
Size and Type	336 x 28 (13.2 x 1.1) vented disc with 54 (2.13) two-piston pin-slider caliper and anti-lock braking system (ABS)
Swept Area	1,884 sq. cm (292 sq. in.)
Rear	
Size and Type	352 x 22 (13.8 x 0.87) disc with 54 (2.13) single-piston pin-slider caliper and ABS
Swept Area	1,768 sq. cm (274 sq. in.)
Power-assist	Dual-rate, tandem diaphragm vacuum

AIR BAGS

Regular Cab	6
Quad Cab	6
Crew Cab	6



2016 RAM 1500 CANADIAN SPECIFICATIONS

STEERING

Power-assist

Regular Cab	2WD	2WD	4WD	4WD
Box Length	6-ft. 4-in.	8-ft.	6-ft. 4-in.	8-ft.
Wheelbase (nominal)	3,061 (120.5)	3,569.2 (140.5)	3,061 (120.5)	3,569.2 (140.5)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire	12.0 m (39.5 ft.)	13.7 m (45.1 ft.)	12.1 m (39.8 ft.)	13.8 m (45.4 ft.)
Turning Diameter – 20-in. Tire	12.0 m (39.3 ft.)	13.7 m (44.9 ft.)	12.1 m (39.8 ft.)	13.9 m (45.5 ft.)
Turning Diameter – 17-in. Outdoorsman Tire	N/A	N/A	12.0 m (39.4 ft.)	13.7 m (45.0 ft.)

Quad Cab	2WD	4WD
Box Length	6-ft. 4-in.	6-ft. 4-in.
Wheelbase (nominal)	3,569.2 (140.5)	3,569.2 (140.5)
Overall Steering Ratio	17.9:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter – 17-in. Tire	13.7 m (45.1 ft.)	13.8 m (45.4 ft.)
Turning Diameter – 20-in. Tire	13.7 m (44.9 ft.)	13.9 m (45.5 ft.)
Turning Diameter – 17-in. Outdoorsman Tire	13.7 m (44.8 ft.)	13.7 m (45.0 ft.)

Crew Cab	2WD	2WD	4WD	4WD
Box Length	5-ft. 7-in.	6-ft. 4-in.	5-ft. 7-in.	6-ft. 4-in.
Wheelbase (nominal)	3,061 (140.5)	3,569.2 (149.5)	3,569.2 (140.5)	3,569.2 (149.5)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire	12.0 m (39.5 ft.)	13.7 m (45.1 ft.)	12.1 m (39.8 ft.)	13.8 m (45.4 ft.)
Turning Diameter – 20-in. Tire	12.0 m (39.3 ft.)	13.7 m (44.9 ft.)	12.1 m (39.8 ft.)	13.9 m (45.5 ft.)
Turning Diameter – 17-in. Outdoorsman Tire	N/A	N/A	12.0 m (39.4 ft.)	13.7 m (45.0 ft.)



2016 RAM 1500 CANADIAN SPECIFICATIONS

DIMENSIONS AND CAPACITIES mm (in.) unless otherwise noted

Cargo Box

Nominal Box Size	5-ft. 7-in. (Crew)	6-ft. 4-in. (Regular, Quad, or Crew)	8-ft. (Regular)
Volume	1,424 litres (50.3 cu.ft.)	1,628 litres (57.5 cu.ft.)	2,115 litres (74.7 cu.ft.)
Length at Floor, Tailgate Closed	1,712.4 (67.4)	1,938.5 (76.3)	2,496.5 (98.3)
Cargo Width	1,686.9 (66.4)	1,686.9 (66.4)	1,686.9 (66.4)
Distance Between Wheelhouses	1,295.4 (51)	1,295.4 (51)	1,295.4 (51)
Depth	508.6 (20.0)	511.1 (20.1)	513.0 (20.2)
Tailgate Opening Width	1535.3 (60.4)	1535.3 (60.4)	1535.3 (60.4)

Regular Cab Pickup

Model – Tire Size	2WD –265/70R17		4WD –265/70R17	
Box Length	6-ft. 4-in.	8-ft.	6-ft. 4-in.	8-ft.
Wheelbase (nominal)	3,061.2 (120.5)	3,569.2 (140.5)	3,062.5 (120.5)	3,570.2 (140.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,732.3 (68.2)	1,732.3 (68.2)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,308.5 (209.0)	5,866.5 (231.0)	5,308.5 (209.0)	5,866.5 (231.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,894.2 (74.6)	1,889.2 (74.4)	1,910.4 (75.2)	1,906.2 (75.0)
Ground Clearance				
Front Axle	229.3 (9.0)	229.2 (9.0)	232.6 (9.2)	232.7 (9.2)
Rear Axle	221.2 (8.7)	221.5 (8.7)	219.2 (8.6)	219.5 (8.6)
Open Tailgate to Ground	883.4 (34.8)	878.3 (34.6)	889.6 (35.0)	885.3 (34.9)
Pickup Body Height	511.1 (20.1)	513.0 (20.2)	511.1 (20.1)	513.0 (20.2)
Approach Angle (degrees)	15.6	15.7	17.7	17.8
Departure Angle (degrees)	25.2	24.1	25.6	24.4
Ramp Breakover Angle (degrees)	21.5	19.2	22.9	20.5
Fuel-Tank Capacity	98-litre (standard)	121-litre (standard)	98-litre (standard)	121-litre (standard)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Quad Cab 6-ft. 4-in. Box Pickup

<i>Model – Tire Size</i>	<i>2WD –265/70R17</i>	<i>4WD –265/70R17</i>
Wheelbase (nominal)	3,569.2 (140.5)	3,570.2 (140.5)
Track, Front	1,728.2 (68.0)	1,732.3 (68.2)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,960.2 (77.2)	1,974.8 (77.7)
Ground Clearance		
Front Axle	229.2 (9.0)	232.7 (9.2)
Rear Axle	221.5 (8.7)	219.5 (8.6)
Open tailgate to ground	878.3 (34.6)	885.3 (34.9)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	15.7	17.8
Departure Angle (degrees)	25.1	25.4
Ramp Breakover Angle (degrees)	19.2	20.5
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)

<i>Model – Tire Size</i>	<i>2WD –265/70R17</i>		<i>4WD –265/70R17</i>	
	<i>6-ft. 4-in.</i>	<i>8-ft.</i>	<i>6-ft. 4-in.</i>	<i>8-ft.</i>
Ground Clearance				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.2	23.6
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab Pickup

Model – Tire Size	2WD –265/70R17		4WD –265/70R17	
	5-ft. 7-in.	6-ft. 4-in.	5-ft. 7-in.	6-ft. 4-in.
Box Length				
Wheelbase (nominal)	3,569.2 (140.5)	3,795.3 (149.4)	3,570.2 (140.5)	3,795.2 (149.4)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,732.3 (68.2)	1,732.3 (68.2)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	6,042.6 (237.9)	5,816.5 (229.0)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,016.6 (79.4)	2,017.4 (79.4)	2,016.6 (79.4)
Overall Height	1,953.8 (76.9)	1,950.6 (76.8)	1,967.9 (77.5)	1,965.1 (77.4)
Ground Clearance				
Front Axle	229.2 (9.0)	231.1 (9.1)	232.7 (9.2)	235.2 (9.2)
Rear Axle	221.5 (8.7)	220.5 (8.7)	219.5 (8.6)	218.3 (8.6)
Open Tailgate to Ground	878.3 (34.6)	874.0 (34.4)	885.3 (34.9)	880.8 (34.7)
Pickup Body Height	508.6 (20.0)	511.1 (20.1)	508.6 (20.0)	511.1 (20.1)
Approach Angle (degrees)	15.7	16.0	17.8	18.0
Departure Angle (degrees)	25.1	24.9	24.7	25.2
Ramp Breakover Angle (degrees)	19.2	18.5	20.5	19.7
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab Pickup – Outdoorsman

<i>Model – Tire Size</i>	<i>2WD – 275/60R20</i>		<i>4WD – 275/60R20</i>	
Box Length	5-ft. 7-in.	6-ft. 4-in.	5-ft. 7-in.	6-ft. 4-in.
Wheelbase (nominal)	3,569.4 (140.5)	3,795.8 (149.4)	3,573.5 (140.7)	3,799.6 (149.6)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,743.2 (68.6)	1,743.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	6,042.6 (237.9)	5,816.5 (229.0)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,016.6 (79.4)	2,017.4 (79.4)	2,016.6 (79.4)
Overall Height	1,972.3 (77.6)	1,968.1 (77.5)	1,994.1 (78.5)	1,991.7 (78.4)
Ground Clearance				
Front Axle	244.8 (9.6)	243.6 (9.6)	248.6 (9.8)	248.0 (9.8)
Rear Axle	237.0 (9.3)	235.0 (9.3)	233.2 (9.2)	233.1 (9.2)
Open Tailgate to Ground	887.7 (34.9)	883.9 (34.8)	903.5 (35.6)	902.3 (35.5)
Pickup Body Height	508.6 (20.0)	511.1 (20.1)	508.6 (20.0)	511.1 (20.1)
Approach Angle (degrees)	21.3	21.0	23.9	22.9
Departure Angle (degrees)	21.4	21.2	22.1	22.1
Ramp Breakover Angle (degrees)	20.9	19.9	18.8	17.6
Ground Clearance without Skid Plate	261.5 (10.3)	261.0 (10.3)	NA	NA
Ground Clearance with Skid Plate	NA	NA	252.2 (9.9)	251.6 (9.9)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,902.1 (74.9)	1,955.1 (77.0)	1,979.2 (77.9)	2,006.1 (79.0)
Ground Clearance				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,917.4 (75.5)	1,970.4 (77.6)	1,994.5 (78.5)	2,021.4 (79.6)
Ground Clearance				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,902.1 (74.9)	1,955.1 (77.0)	1,979.2 (77.9)	2,006.1 (79.0)
Ground Clearance				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.7	21.8	22.9
Departure Angle (degrees)	18.7	20.6	21.4	22.9
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0
Ramp Breakover Angle with Skid Plate	12.7	15.9	17.6	19.2
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,917.4 (75.5)	1,970.4 (77.6)	1,994.5 (78.5)	2,021.4 (79.6)
Ground Clearance				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.2	23.6
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,897.7 (74.7)	1,950.7 (76.8)	1,975.2 (77.8)	2,001.7 (78.8)
Ground Clearance				
Front Axle	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)
Rear Axle	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)
Open Tailgate to Ground	827.9 (32.6)	866.6 (34.1)	885.2 (34.8)	917.6 (36.1)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	22.8	24.6	25.5	26.9
Ramp Breakover Angle (degrees)	15.3	18.7	20.5	22.2
Ground Clearance without Skid Plate	170.0 (6.7)	222.7 (8.8)	252.4 (9.9)	273.7 (10.8)
Ground Clearance with Skid Plate	152.3 (6.0)	205.4 (8.1)	235.4 (9.3)	256.4 (10.1)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,914.5 (75.4)	1,967.5 (77.5)	1,991.9 (78.4)	2,018.5 (79.5)
Ground Clearance				
Front Axle	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)
Rear Axle	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)
Open Tailgate to Ground	819.5 (32.3)	883.9 (34.8)	902.5 (35.5)	934.9 (36.8)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	15.5	19.7	22.3	23.9
Departure Angle (degrees)	22.5	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	16.4	19.8	21.7	23.3
Ground Clearance without Skid Plate	185.8 (7.3)	239.0 (9.4)	268.7 (10.6)	290.0 (11.4)
Ground Clearance with Skid Plate	168.8 (6.6)	221.7 (8.7)	251.7 (9.9)	272.7 (10.7)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,897.7 (74.7)	1,950.7 (76.8)	1,975.2 (77.8)	2,001.7 (78.8)
Ground Clearance				
Front Axle	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)
Rear Axle	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)
Open Tailgate to Ground	827.9 (32.6)	866.6 (34.1)	885.2 (34.8)	917.6 (36.1)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	15.3	19.7	21.8	22.9
Departure Angle (degrees)	18.6	20.4	21.3	22.7
Ramp Breakover Angle without Skid Plate	15.3	18.7	20.5	22.2
Ramp Breakover Angle with Skid Plate	12.0	15.0	16.6	18.2
Ground Clearance without Skid Plate	170.0 (6.7)	222.7 (8.8)	252.4 (9.9)	273.7 (10.8)
Ground Clearance with Skid Plate	152.3 (6.0)	205.4 (8.1)	235.4 (9.3)	256.4 (10.1)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,914.5 (75.4)	1,967.5 (77.5)	1,991.9 (78.4)	2,018.5 (79.5)
Ground Clearance				
Front Axle	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)
Rear Axle	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)
Open Tailgate to Ground	819.5 (32.3)	883.9 (34.8)	902.5 (35.5)	934.9 (36.8)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.1	23.6
Ramp Breakover Angle without Skid Plate	16.4	19.8	21.7	23.3
Ramp Breakover Angle with Skid Plate	13.0	16.0	17.7	19.2
Ground Clearance without Skid Plate	185.8 (7.3)	239.0 (9.4)	268.7 (10.6)	290.0 (11.4)
Ground Clearance with Skid Plate	168.8 (6.6)	221.7 (8.7)	251.7 (9.9)	272.7 (10.7)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

ACCOMMODATIONS mm (in.) unless otherwise noted

Model	Regular Cab	Quad Cab	Crew Cab
Seating Capacity, F/R	3/0 or 2/0	3/3 or 2/3	3/3 or 2/3
Front			
Head Room	1,013.5 (39.9)	1,041.4 (41.0)	1,041.4 (41.0)
Legroom	1,041.4 (41.0)	1,041.4 (41.0)	1,041.4 (41.0)
Shoulder Room	1,676.4 (66.0)	1,676.4 (66.0)	1,676.4 (66.0)
Hip Room	1,598.7 (62.9)	1,605.3 (63.2)	1,605.3 (63.2)
Seat Travel	230.0 (9.0)	230.0 (9.0)	230.0 (9.0)
Recliner Range (degrees)	85 (38 RWD, 47 FWD)	56 (38 RWD 18 FWD)	56 (38 RWD, 18 FWD)
Rear			
Head Room	N/A	1,008.4 (39.7)	1,013.5 (39.9)
Legroom	N/A	880.9 (34.7)	1,023.3 (40.3)
Shoulder Room	N/A	1,668.8 (65.7)	1,668.8 (65.7)
Hip Room	N/A	1,598.3 (62.9)	1,605.3 (63.2)
Interior Volume			
Front	1,770 litres (62.5 cu.ft.)	1,880 litres (64.2 cu.ft.)	1,880 litres (64.2 cu.ft.)
Rear	N/A	1,484 litres (52.4 cu.ft.)	1,730 litres (61.1 cu.ft.)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Quad Cab 6ft. 4in. Box Pickup – Outdoorsman

Model – Tire Size	2WD –275/60R20	4WD –275/60R20
Wheelbase (nominal)	3,569.4 (140.5)	3,573.5 (140.7)
Track, Front	1,742.2 (68.6)	1,743.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,979.4 (77.9)	2,001.6 (78.8)
Ground Clearance		
Front Axle	244.8 (9.6)	248.6 (9.8)
Rear Axle	237.0 (9.3)	233.2 (9.2)
Open tailgate to ground	887.7 (34.9)	903.5 (35.6)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	21.3	23.9
Departure Angle, (degrees)	21.4	22.1
Ramp Breakover Angle (degrees)	20.9	18.8
Ground Clearance without Skid Plate	261.5 (10.3)	NA
Ground Clearance with Skid Plate	NA	252.2 (9.9)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,909.0 (75.2)	1,962.0 (77.2)	1,986.6 (78.2)	2,013.0 (79.2)
Ground Clearance				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,924.4 (75.8)	1,977.4 (77.8)	2,002.0 (78.8)	2,028.4 (79.9)
Ground Clearance				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,909.0 (75.2)	1,962.0 (77.2)	1,986.6 (78.2)	2,013.0 (79.2)
Ground Clearance				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.7	21.8	22.9
Departure Angle (degrees)	18.7	20.6	21.4	22.9
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0
Ramp Breakover Angle, with Skid Plate	12.7	15.9	17.6	19.2
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,924.4 (75.8)	1,977.4 (77.8)	2,002.0 (78.8)	2,028.4 (79.9)

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x4 Rebel

<i>Tire Size</i>	<i>285/70R17</i>		
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,070.8 (81.5)	2,070.8 (81.5)	2,070.8 (81.5)
Overall Height	1,913.7 (75.3)	1,984.6 (78.1)	2,010.2 (79.1)
Ground Clearance			
Front Axle	237.3 (9.3)	237.3 (9.3)	237.3 (9.3)
Rear Axle	223.6 (8.8)	223.6 (8.8)	223.6 (8.8)
Lift In Height	835.3 (32.9)	899.1 (35.4)	924.7 (36.4)
Pickup Box Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle, degrees	18.7	23.8	25.3
Departure Angle, degrees	18.9	21.9	23.0
Ramp Breakover Angle without Skid Plate, degrees	17.7	23.6	25.4
Ramp Breakover Angle with Skid Plate, degrees	13.0	18.0	19.6
Ground Clearance without Skid Plate	175.5 (6.9)	253.5 (10.0)	279.1 (11.0)
Ground Clearance with Skid Plate	157.8 (6.2)	236.3 (9.3)	261.9 (10.3)
Fuel-Tank Capacity	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)	98-litre (standard) 121-litre (optional)



2016 RAM 1500 CANADIAN SPECIFICATIONS

Cargo Box

Nominal Box Size	5 ft. 7 in.
Volume	1,424.3 litres (50.3 cu.ft.)
Length at Floor, Tailgate Closed	1,712.4 (67.4)
Cargo Width	1,686.9 (66.4)
Distance Between Wheelhouses	1,295.4 (51)
Depth	508.6 (20.0)
Tailgate Opening Width in.	1,535.3 (60.4)

ACCOMMODATIONS mm (in.) unless otherwise noted

<i>Model</i>	<i>Crew Cab</i>
Seating Capacity, F/R	2/3
Front	
Head Room	1,040.5 (41.0)
Legroom	1,039.6 (40.9)
Shoulder Room	1,674.9 (65.9)
Hip Room	1,598.1 (62.9)
Seat Travel	230.0 (9.0)
Recliner Range, degrees	56° (38 RWD, 18 FWD)
Rear	
Head Room	1,013.5 (39.9)
Legroom	1,022.3 (40.2)
Shoulder Room	1,670 (65.7)
Hip Room	1,592.7 (62.7)
Interior Volume	
Front	1,815.1 litres (64.0 cu.ft.)
Rear	1,727.3 litres (61.0 cu.ft.)

