



RAM

2017 RAM 1500  
CANADIAN  
SPECIFICATIONS

17

FCA CANADA  
2017 Ram 1500  
CANADIAN SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.  
All dimensions are in millimetres (inches) unless otherwise noted.  
All dimensions measured at curb weight with standard tires and wheels.*

**GENERAL INFORMATION**

Vehicle Type	Regular Cab, Quad Cab and Crew Cab, 2WD, 4WD
Assembly Plant	Regular Cab: Saltillo, Coahuila, Mexico Quad Cab: Warren, Michigan Crew Cab: Warren, Michigan and Saltillo, Coahuila, Mexico
EPA Vehicle Class	Standard Pickup

**BODY/CHASSIS**

Layout	2WD — Longitudinal, front engine 4WD — Longitudinal, front engine, transfer case
Construction	2WD — Ladder-type frame, steel cab, double-wall steel pickup box 4WD — Ladder-type frame, steel cab, double-wall steel pickup box

**ENGINE: 3.6-LITRE PENTASTAR V6**

Type and Description	60-degree V-type, liquid-cooled
Displacement	3,604 cu. cm (220 cu. in.)
Bore x Stroke	96 x 83 (3.78 x 3.27)
Valve System	Chain-driven DOHC, 24 valves and hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	10.2:1
Power	305 hp (224 kW) at 6,400 rpm
Torque	269 lb.-ft. (364 N•m) at 4,175 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2, E85-compatible
Oil Capacity	5.7 litres (6.0 quarts)
Coolant Capacity	13.25 litres (14.0 quarts)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors



RAM

2017 RAM 1500  
CANADIAN  
SPECIFICATIONS

17

EnerGuide (2016) Fuel Consumption Ratings L/100 km (MPG – imperial gallon) city/hwy	13.9/9.5 (20/30) – 4x2 models 14.6/10.1 (19/28) – 4x4 models
---	---

Based on 2016 EnerGuide fuel consumption ratings. Government of Canada test methods used. Your actual fuel consumption will vary based on and other factors. For EnerGuide information, please visit the Government of Canada website: [www.vehicles.nrcan.gc.ca](http://www.vehicles.nrcan.gc.ca)

**ENGINE: 3.0-LITRE ECODIESEL V6**

Type and Description	60-degree V-type, liquid-cooled
Displacement	2,999 cu. cm (182 cu. in.)
Bore x Stroke	83 x 92 (3.27 x 3.60)
Valve System	Chain-driven DOHC, 24 valves
Fuel Injection	Common-rail, 2,000 bar, solenoid injectors
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	16.5:1
Power	240 hp (179 kW) at 3,600 rpm
Torque	420 lb.-ft. (569 N•m) at 2,000 rpm
Max. Engine Speed	4,800 rpm (electronically limited)
Fuel Requirement	Ultra-low sulfur diesel
Oil Capacity	10 litres (10.5 quarts)
Coolant Capacity	11.4 litres (12 quarts)
Emission Controls	Cooled EGR, oxidation catalyst, diesel particulate filter, SCR w/urea injection
EnerGuide (2016) Fuel Consumption Ratings L/100 km (MPG – imperial gallon) city/hwy	11.3/8.0 (25/35) – 4x2 HFE models 11.6/8.4 (24/34) – 4x2 non-HFE models 12.1/8.8 (23/32) – 4x4 models

**ENGINE: 5.7-LITRE HEMI® V8**

Type and Description	90-degree V8, liquid-cooled
Displacement	5,654 cu. cm (345 cu. in.)
Bore x Stroke	99.5 x 90.9 (3.92 x 3.58)
Valve System	Variable-cam timing, pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
Power	395 hp (291 kW) @ 5,600 rpm



**RAM**

2017 RAM 1500  
**CANADIAN  
SPECIFICATIONS**



Torque	410 lb.-ft. (556 N•m) @ 3,950 rpm
Max. Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — recommended Unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	6.6 litres (7.0 quarts)
Coolant Capacity	13.3 litres (14.0 quarts)
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features
EnerGuide (2016) Fuel Consumption Ratings L/100 km (MPG – imperial gallon) city/hwy	15.8 (18) / 10.9 (26) — 4x2 models 16.2 (17) / 11.5 (25) — 4x4 models
EnerGuide (2016) Fuel Consumption Ratings L/100 km (MPG – imperial gallon) city/hwy	17.1 (17) / 12.0 (24) — 4x2 models 17.7 (16) / 12.7 (22) — 4x4 models

**TRANSMISSION: 65RFE AUTOMATIC SIX-SPEED**

Availability	Available with 5.7-litre HEMI V8 equipped trucks
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
<b>Gear Ratios</b>	
1st	3.00
2nd	1.67
3rd	1.50
4th	1.00
5th	0.75
6th	0.67
Reverse	3.00
Axle Gear Ratios	3.21, 3.55, 3.92,

**TRANSMISSION: TORQUEFLITE 845RE EIGHT-SPEED AUTOMATIC**

Availability	Standard with 3.6-litre Pentastar V6
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
<b>Gear Ratios</b>	
1st	4.71
2nd	3.14
3rd	2.10



2017 RAM 1500  
**CANADIAN  
SPECIFICATIONS**

17

4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Gear Ratios	3.21, 3.55, 3.92 (Rebel only)

**TRANSMISSION: TORQUEFLITE 8HP70 EIGHT-SPEED AUTOMATIC**

Availability	Standard with 3.0-litre EcoDiesel V6 and select 5.7-litre HEMI V8 equipped trucks
Description	Adaptive electronic control, automatic or ERS manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Gear Ratios	3.21 (excluding 3.0-litre EcoDiesel V6), 3.55 (excluding 5.7-litre HEMI V8), 3.92

**TRANSFER CASE: BW 44-45 PART-TIME**

Availability	3.0-litre EcoDiesel V6 4x4, 3.6-litre Pentastar V6 4x4 and 5.7-litre HEMI V8 4x4
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Center Differential Type	None



2017 RAM 1500  
CANADIAN  
SPECIFICATIONS



**TRANSFER CASE: BW 44-44 ON-DEMAND**

Availability	3.0-litre EcoDiesel V6 4x4, 3.6-litre Pentastar V6 4x4 and 5.7-litre HEMI V8 4x4
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD Auto; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Center Differential Type	None

**AXLES**

Front	ZF 215 mm
Rear	C235 mm (available limited slip)
Available Ratios	3.21, 3.55, 3.92

**ELECTRICAL SYSTEM**

Architecture	Powernet
Alternator	160-amp, 180-amp, 220-amp (Stop-start system and Special Services Package) 230-amp (3.0-liter EcoDiesel V6)
Battery	Group 65, low-maintenance 730 CCA (Stop-start features 800 CCA absorbed glass mat)

**SUSPENSION**

Front	Upper and lower A-arms, coil springs, twin-tube shock absorbers, stabilizer bar. Optional air suspension replaces twin-tube shock absorbers and coil springs. Rebel features Bilstein monotube shocks with air suspension
Rear	Five-link with track bar, coil springs, stabilizer bar, twin-tube shock absorbers, solid axle. Optional air suspension replaces twin-tube shock absorbers and coil springs. Rebel features Bilstein monotube shocks with air suspension

**BRAKES**

Front	
Size and Type	336 x 28 (13.2 x 1.1) vented disc with 54 (2.13) Two-piston pin-slider caliper and anti-lock braking system (ABS)
Swept Area	1,884 sq. cm (292 sq. in.)
Rear	
Size and Type	352 x 22 (13.8 x 0.87) disc with 54 (2.13) Single-piston pin-slider caliper and ABS
Swept Area	1,768 sq. cm (274 sq. in.)
Power-assist	Dual-rate, tandem diaphragm vacuum



**RAM**

2017 RAM 1500  
**CANADIAN  
SPECIFICATIONS**

**17**

**AIR BAGS**

Regular Cab	6
Quad Cab	6
Crew Cab	6

**STEERING**

Power-assist

<b>Regular Cab</b>	<b>2WD</b>	<b>2WD</b>	<b>4WD</b>	<b>4WD</b>
Box Length	6-ft. 4-in.	8-ft.	6-ft. 4-in.	8-ft.
Wheelbase (nominal)	3,061 (120.5)	3,569.2 (140.5)	3,061 (120.5)	3,569.2 (140.5)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire -m (ft.)	12.0 (39.5)	13.7 (45.1)	12.1 (39.8)	13.8 (45.4)
Turning Diameter – 20-in. Tire - m (ft.)	12.0 (39.3)	13.7 (44.9)	12.1 (39.8)	13.9 (45.5)

<b>Quad Cab</b>	<b>2WD</b>	<b>4WD</b>
Box Length	6-ft. 4-in.	6-ft. 4-in.
Wheelbase (nominal)	3,569.2 (140.5)	3,569.2 (140.5)
Overall Steering Ratio	17.9:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter – 17-in. Tire – m (ft.)	13.7 (45.1)	13.8 (45.4)
Turning Diameter – 20-in. Tire – m (ft.)	13.7 (44.9)	13.9 (45.5)

<b>Crew Cab</b>	<b>2WD</b>	<b>2WD</b>	<b>4WD</b>	<b>4WD</b>
Box Length	5-ft. 7-in.	6-ft. 4-in.	5-ft. 7-in.	6-ft. 4-in.
Wheelbase (nominal)	3,569.2 (140.5)	3,797.3 (149.5)	3,569.2 (140.5)	3,797.3 (149.5)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire -m (ft.)	12.0 (39.5)	13.7 (45.1)	12.1 (39.8)	13.8 (45.4)
Turning Diameter – 20-in. Tire – m (ft.)	12.0 (39.3)	13.7 (44.9)	12.1 (39.8)	13.9 (45.5)



2017 RAM 1500  
CANADIAN  
SPECIFICATIONS



**DIMENSIONS AND CAPACITIES**

**Cargo Box**

<b>Nominal Box Size</b>	<b>5-ft. 7-in. (Crew)</b>	<b>6-ft. 4-in. (Regular, Quad or Crew)</b>	<b>8-ft. (Regular)</b>
SAE volume, litres (cu. ft.)	1,424 (50.3)	1,628 (57.5)	2,115 (74.7)
Length at Floor, Tailgate Closed	1,712.4 (67.4)	1,938.5 (76.3)	2,496.5 (98.3)
Cargo Width	1,686.9 (66.4)	1,686.9 (66.4)	1,686.9 (66.4)
Distance Between Wheelhouses	1,295.4 (51)	1,295.4 (51)	1,295.4 (51)
Depth	508.6 (20.0)	511.1 (20.1)	513.0 (20.2)
Tailgate Opening Width	1,535.3 (60.4)	1,535.3 (60.4)	1,535.3 (60.4)

**Regular Cab Pickup**

<b>Model – Tire Size</b>	<b>2WD –265/70R17</b>		<b>4WD –265/70R17</b>	
	<b>6-ft. 4-in.</b>	<b>8-ft.</b>	<b>6-ft. 4-in.</b>	<b>8-ft.</b>
Box Length				
Wheelbase (nominal)	3,061.2 (120.5)	3,569.2 (140.5)	3,062.5 (120.5)	3,570.2 (140.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,732.3 (68.2)	1,732.3 (68.2)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,308.5 (209.0)	5,866.5 (231.0)	5,308.5 (209.0)	5,866.5 (231.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,894.2 (74.6)	1,889.2 (74.4)	1,910.4 (75.2)	1,906 (75.0)

**Ground Clearance**

Front Axle	229.3 (9.0)	229.2 (9.0)	232.6 (9.2) (232.6)	232.7 (9.2)
Rear Axle	221.2 (8.7)	221.5 (8.7)	219.2 (8.6) (219.2)	219.5 (8.6)
Open Tailgate to Ground	883.4 (34.8)	878.3 (34.6)	889.6 (35.0) (889.6)	885.3 (34.9)
Pickup Body Height	511.1 (20.1)	513.0 (20.2)	511.1 (20.1) (511.1)	513.0 (20.2)
Approach Angle (degrees)	15.6	15.7	17.7	17.8
Departure Angle (degrees)	25.2	24.1	25.6	24.4
Box Length	<b>6-ft. 4-in.</b>	<b>8-ft.</b>	<b>6-ft. 4-in.</b>	<b>8-ft.</b>
Ramp Breakover Angle (degrees)	21.5	19.2	22.9	20.5
Fuel-Tank Capacity	98 litres (26 gal.) (standard)	121 litres (32 gal.) (standard)	98 litres (26 gal.) (standard)	121 litres (32 gal.) (standard)



2017 RAM 1500  
CANADIAN  
SPECIFICATIONS



**Quad Cab 6-ft. 4-in. Box Pickup**

<b>Model – Tire Size</b>	<b>2WD –265/70R17</b>	<b>4WD –265/70R17</b>
Box Length	6-ft. 4-in.	6-ft. 4-in.
Wheelbase (nominal)	3,569.2 (140.5)	3,570 (140.5)
Track, Front	1,728.2 (68.0)	1,732.3 (68.2)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,960.2 (77.2)	1,974.8 (77.7)
Box Length	6-ft. 4-in.	6-ft. 4-in.
<b>Ground Clearance</b>		
Front Axle	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	904.1 (35.6)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	16.6	22.9
Departure Angle (degrees)	19.4	22.2
Ramp Breakover Angle without Skid Plate	17.1	22.5
Ramp Breakover Angle with Skid Plate	13.8	18.7
Ground Clearance without Skid Plate	187.2 (7.4)	269.5 (10.6)
Ground Clearance with Skid Plate	169.3 (6.7)	252.8 (9.9)
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)
	121 litres (optional)	121 litres (optional)

**Quad Cab 6-ft. 4-in. Box Pickup - Air Suspension 4x2 and 4x4**

<b>Tire Size</b>	<b>265/70R17</b>			
<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5))	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,909.0 (75.2)	1,962.0 (77.2)	1,986.6 (78.2)	2,013.0 (79.2)



**RAM**

2017 RAM 1500  
**CANADIAN  
 SPECIFICATIONS**

**17****Ground Clearance**

Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)	98 litres (standard)	98 litres (standard)
	121 litres (optional)	121 litres (optional)	121 litres (optional)	121 litres (optional)

**Quad Cab 6-ft. 4-in. Box Pickup - Air Suspension 4x2 and 4x4****Tire Size****275/60R20**

<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	79.4 (2,017.4) 2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,924.4 (75.8)	1977.4 (77.8)	2002.0 (78.8)	2,028.4 (79.9)

**Ground Clearance**

Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2

**RAM**

2017 RAM 1500  
**CANADIAN  
 SPECIFICATIONS**

**17****Quad Cab 6-ft. 4-in. Box Pickup - Air Suspension 4x2 and 4x4 (continued)**

<i>Tire Size</i>	<i>275/60R20</i>			
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)	98 litres (standard)	98 litres (standard)
	121 litres (optional)	121 litres (optional)	121 litres (optional)	121 litres (optional)

**Crew Cab Pickup**

<i>Model – Tire Size</i>	<i>2WD – 265/70R17</i>		<i>4WD – 265/70R17</i>	
	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>
Box Length				
Wheelbase (nominal)	3,569.2 (140.5)	3,795.3 (149.4) (3,795.3)	3,570.2 (140.5) (3,570.2)	3,795.2 (149.4) (3,795.2)
Track, Front	1,728.2 (68.0) (1,728.2)	1,728.2 (68.0)	1,732.3 (68.2)	1,732.3 (68.2)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	5,816.5 (229.0)	6,042.6 (237.9)	5,816.5 (229.0)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,016.6 (79.4)	2,017.4 (79.4)	2,016.6 (79.4)
Overall Height	1,953.8 (76.9)	1,950.6 (76.8)	1,967.9 (77.5)	1,965.1 (77.4)
<b>Ground Clearance</b>				
Front Axle	229.2 (9.0)	231.1 (9.1)	232.7 (9.2)	235.2 (9.2)
Rear Axle	221.5 (8.7)	220.5 (8.7)	219.5 (8.6)	218.3 (8.6)
Open Tailgate to Ground	878.3 (34.6)	874.0 (34.4)	885.3 (34.9)	880.8 (34.7)
Box Length	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>
Pickup Body Height	508.6 (20.0)	511.1 (20.1)	508.6 (20.0)	511.1 (20.1)
Approach Angle (degrees)	15.7	16.0	17.8	18.0
Departure Angle (degrees)	25.1	24.9	24.7	25.2
Ramp Breakover Angle (degrees)	19.2	18.5	20.5	19.7
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)	98 litres (standard)	98 litres (standard)
	121 litres (optional)	121 litres (optional)	121 litres (optional)	121 litres (optional)



2017 RAM 1500  
CANADIAN  
SPECIFICATIONS



**Crew Cab 5-ft. 7-in. Box Pickup - Air Suspension 4x2 and 4x4**

<i>Tire Size</i>		<i>265/70R17</i>			
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>	
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	
Track, Front	1,728.2 (68.0) (1,728.2)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	
Overall Height	1,902.1 (74.9)	1,955.1 (77.0)	1,979.2 (77.9)	2,006.1 (79.0)	
<b>Ground Clearance</b>					
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	
Open Tailgate to Ground	832.8 (32.8) (832.8)	871.2 (34.3) (871.2)	889.6 (35.0)	922.2 (36.3)	
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	
Approach Angle (degrees)	13.8	18.3	20.9	22.5	
Departure Angle (degrees)	23.0	24.8	25.6	27.1	
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0	
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254.0 (10.0)	274.3 (10.8)	
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)	
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)	98 litres (standard)	98 litres (standard)	
	121 litres (optional)	121 litres (optional)	121 litres (optional)	121 litres (optional)	



2017 RAM 1500  
CANADIAN  
SPECIFICATIONS



**Crew Cab 5-ft. 7-in. Box Pickup - Air Suspension 4x2 and 4x4**

<b>Tire Size</b>		<b>275/60R20</b>		
<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,917.4 (75.5)	1,970.4 (77.6)	1,994.5 (78.5)	2,021.4 (79.6)
<b>Ground Clearance</b>				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)	98 litres (standard)	98 litres (standard)
	121 litres (optional)	121 litres (optional)	121 litres (optional)	121 litres (optional)

**RAM**

2017 RAM 1500  
**CANADIAN  
 SPECIFICATIONS**

**17****Crew Cab 6-ft. 4-in. Box Pickup - Air Suspension 4x2 and 4x4**

<i>Tire Size</i>	<i>265/70R17</i>			
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,798.0 (149.5) )	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)
Track, Front	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)	1,728.2 (68.0)
Track, Rear	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)	1,714.7 (67.5)
Overall Length	6,042.6 (237.9) )	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)
Overall Height	1,897.7 (74.7)	1,950.7 (76.8)	1,975.2 (77.8)	2,001.7 (78.8)
<b>Ground Clearance</b>				
Front Axle	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)
Rear Axle	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)
Open Tailgate to Ground	827.9 (32.6)	866.6 (34.1)	885.2 (34.8)	917.6 (36.1)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	22.8	24.6	25.5	26.9
Ramp Breakover Angle (degrees)	15.3	18.7	20.5	22.2
Ground Clearance without Skid Plate	170.0 (6.7)	222.7 (8.8)	252.4 (9.9)	273.7 (10.8)
Ground Clearance with Skid Plate	152.3 (6.0)	205.4 (8.1)	235.4 (9.3)	256.4 (10.1)
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)	98 litres (standard)	98 litres (standard)
	121 litres (optional)	121 litres (optional)	121 litres (optional)	121 litres (optional)

**Crew Cab 6-ft. 4-in. Box Pickup - Air Suspension 4x2 and 4x4**

<i>Tire Size</i>	<i>275/60R20</i>			
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)	3,798.0 (149.5)
Track, Front	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)	1,742.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)	6,042.6 (237.9)
Overall Width	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)	2,017.4 (79.4)



2017 RAM 1500  
CANADIAN  
SPECIFICATIONS



**Crew Cab 6-ft. 4-in. Box Pickup - Air Suspension 4x2 and 4x4 (continued)**

<i>Tire Size</i>	<i>275/60R20</i>			
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Overall Height	1,914.5 (75.4)	1,967.5 (77.5)	1,991.9 (78.4)	2,018.5 (79.5)
<b>Ground Clearance</b>				
Front Axle	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)
Rear Axle	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)
Open Tailgate to Ground	819.5 (32.3)	883.9 (34.8)	902.5 (35.5)	934.9 (36.8)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	15.5	19.7	22.3	23.9
Departure Angle (degrees)	22.5	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	16.4	19.8	21.7	23.3
Ground Clearance without Skid Plate	185.8 (7.3)	239.0 (9.4)	268.7 (10.6)	290.0 (11.4)
Ground Clearance with Skid Plate	168.8 (6.6)	221.7 (8.7)	251.7 (9.9)	272.7 (10.7)
Fuel-Tank Capacity	98 litres (standard)	98 litres (standard)	98 litres (standard)	98 litres (standard)
	121 litres (optional)	121 litres (optional)	121 litres (optional)	121 litres (optional)

**Crew Cab 5-ft. 7-in. Box Pickup - Air Suspension 4x4 Rebel**

<i>Tire Size</i>	<i>285/70R17</i>		
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road</i>
Wheelbase (nominal)	3,569.4 (140.5)	3,569.4 (140.5)	3,569.4 (140.5)
Track, Front	1,743.2 (68.6)	1,743.2 (68.6)	1,743.2 (68.6)
Track, Rear	1,727.4 (68.0)	1,727.4 (68.0)	1,727.4 (68.0)
Overall Length	5,816.5 (229.0)	5,816.5 (229.0)	5,816.5 (229.0)
Overall Width	2,070.8 (81.5)	2,070.8 (81.5)	2,070.8 (81.5)
Overall Height	1,913.7 (75.3)	1,984.6 (78.1)	2,010.2 (79.1)
<b>Ground Clearance</b>			
Front Axle	237.3 (9.3)	237.3 (9.3)	237.3 (9.3)
Rear Axle	223.6 (8.8)	223.6 (8.8)	223.6 (8.8)
Lift In Height	835.3 (32.9)	899.1 (35.4)	924.1 (36.4)
Pickup Box Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)

**RAM**

2017 RAM 1500  
**CANADIAN  
 SPECIFICATIONS**

**17****Crew Cab 5-ft. 7-in. Box Pickup - Air Suspension 4x4 Rebel (continued)**

<i>Tire Size</i>	<i>285/70R17</i>		
<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road</b>
Approach Angle, degrees	18.7	23.8	25.3
Departure Angle, degrees	18.9	21.9	23.0
Ramp Breakover Angle without Skid Plate	17.7	23.6	25.4
Ramp Breakover Angle with Skid Plate	13.0	18.0	19.6
Ground Clearance without Skid Plate	175.5 (6.9)	253.5 (10.0)	279.1 (11.0)
Ground Clearance with Skid Plate	157.8 (6.2)	236.3 (9.3)	261.9 (10.3)
Fuel-Tank Capacity	98 litres (Standard)	98 litres (Standard)	98 litres (Standard)
	121 litres (Optional)	121 litres (Optional)	121 litres (Optional)

**ACCOMMODATIONS**

<b>Model</b>	<b>Regular Cab</b>	<b>Quad Cab</b>	<b>Crew Cab</b>
Seating Capacity, F/R	3/0 or 2/0	3/3 or 2/3	3/3 or 2/3
<b>Front</b>			
Head Room	1,013.4 (39.9)	1,041.4 (41.0)	1,041.4 (41.0)
Legroom	1,041.4 (41.0)	1,041.4 (41.0)	1,041.4 (41.0)
Shoulder Room	1,676.4 (66.0)	1,676.4 (66.0)	1,676.4 (66.0)
Hip Room	1,598.7 (62.9) (1,598.7)	1,605.3 (63.2)	1,605.3 (63.2)
Seat Travel	230.0 (9.0)	230.0 (9.0)	230.0 (9.0)
Recliner Range (degrees)	85 (38 RWD, 47 FWD)	56 (38 RWD 18 FWD)	56 (38 RWD, 18 FWD)
<b>Rear</b>			
Head Room	N/A	1,008.4 (39.7)	1,013.5 (39.9)
Legroom	N/A	880.9 (34.7)	1,023.3 (40.3)
Shoulder Room	N/A	1,668.8 (65.7)	1,668.8 (65.7)
Hip Room	N/A	1,598.3 (62.9)	1,605.3 (63.2)
<b>Interior Volume</b>			
Front – litres (cu. ft.)	1769.8 (62.5)	1817.9 (64.2)	1817.9 (64.2)
Rear – litres (cu. ft.)	N/A	1483.8 (52.4)	1730.1 (61.1)

