



2017 RAM COMMERCIAL 3500 CHASSIS CAB CANADIAN SPECIFICATIONS



FCA CANADA

2017 Ram Commercial 3500 Chassis Cab CANADIAN SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Vehicle Type	Chassis Cab: Regular Cab and Crew Cab
Assembly Plant	Saltillo, Coahuila, Mexico
EPA Vehicle Class	Large Pickup
Introduction	2007 Model Year

ENGINE: 6.4-LITRE HEMI® V8

Availability	Standard
Type and Description	90-degree V-type, liquid-cooled, variable-valve timing (VVT)
Displacement	6,417 cu. cm (392 cu. in.)
Bore x Stroke	103.9 x 94.6 (4.09 x 3.72)
Valve System	Pushrod-operated overhead valves, 16 valves, eight de-activating and eight hydraulic lifters with roller followers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, 356 aluminum cylinder heads with hemispherical combustion chambers
Compression Ratio	10:1
Power	410 hp (302 kW) @ 5,600 rpm Up to 370 hp (267kW) @ 4,600 rpm (over 10k rating)
Torque	429 lb-ft (582 N•m) at 4,000 rpm
Maximum Engine Speed	5,800 rpm limited; 4,800 rpm with AISIN transmission
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	6.6 litres (7 quarts)
Coolant Capacity	15.8 (16.6 quarts)
Emission Control	Three-way catalytic converters, heated oxygen sensors, cooled electronic EGR and individual cylinder fuel control



2017 RAM COMMERCIAL 3500 CHASSIS CAB CANADIAN SPECIFICATIONS



ENGINE: 6.7-LITRE CUMMINS TURBO DIESEL I-6

Availability	Manual six-speed transmission
Type and Description	Inline, liquid-cooled, turbocharged, intercooled
Displacement	6,690 cu cm (408 cu in)
Bore x Stroke	107 x 124 (4.21 x 4.88)
Valve System	Pushrod-operated overhead valves, 24 valves, solid lifters
Fuel Injection	Electronic high-pressure common rail
Construction	Cast-iron block and head
Compression Ratio	17.3:1
Power	320 bhp (239 kW) @ 2,800 rpm
Torque	650 lb-ft (881 N•m) @ 1,400 rpm
Maximum Engine Speed	3,200 rpm
Fuel Requirement	Ultra-low sulfur diesel
Oil Capacity	11.3 litres (12.0 quarts) with filter
Coolant Capacity	22.5 litres (23.8 quarts)
Emission Controls	Selective Catalytic Reduction (SCR)

ENGINE: 6.7-LITRE HIGH OUTPUT CUMMINS TURBO DIESEL I-6

Availability	Optional (AISIN six-speed automatic)
Type and Description	Inline, liquid-cooled, turbocharged, intercooled
Displacement	6,690 cu cm (408 cu in)
Bore x Stroke	107 x 124 (4.21 x 4.88)
Valve System	Pushrod-operated overhead valves, 24 valves, solid lifters
Fuel Injection	Electronic high-pressure common rail
Construction	Cast-iron block and head
Compression Ratio	17.3:1
Power	325 bhp (242 kW) @ 2,400 rpm
Torque	750 lb-ft (1,017 N•m) @ 1,500 rpm
Maximum Engine Speed	3,200 rpm
Fuel Requirement	Ultra-low sulfur diesel
Oil Capacity	11.3 litres (12.0 quarts) with filter
Coolant Capacity	22.5 litres (23.8 quarts)
Emission Controls	Selective Catalytic Reduction (SCR)



2017 RAM COMMERCIAL 3500 CHASSIS CAB
**CANADIAN
SPECIFICATIONS**



TRANSMISSION: G56 — MANUAL SIX-SPEED OVERDRIVE

Availability	6.7-litre diesel
Description	Synchronized in all gears
Gear Ratios	
1st	5.94
2nd	3.28
3rd	1.98
4th	1.31
5th	1.00
6th	0.74
Reverse	5.42
Axle ratios	3.42, 3.73, 4.10
PTO	Left-or right-side with split-shaft capability

TRANSMISSION: 66RFE — AUTOMATIC SIX-SPEED

Availability	6.4-litre HEMI V8
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios	
1st	3.23
2nd	1.84
3rd	1.41
4th	1.00
5th	0.82
6th	0.63
Reverse	4.44
Axle ratios	5.7-liter: 4.10
	6.4-liter: 4.10



2017 RAM COMMERCIAL 3500 CHASSIS CAB
**CANADIAN
SPECIFICATIONS**



TRANSMISSION: AS66RC — AUTOMATIC SIX-SPEED

Availability	6.4-litre HEMI V8
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios	
1st	3.75
2nd	2.00
3rd	1.34
4th	1.00
5th	0.77
6th	0.63
Reverse	3.54
Axle ratios	4.44
PTO	Left- or right-side capability

TRANSMISSION: AS69RC — AUTOMATIC SIX-SPEED

Availability	6.7-litre diesel
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios	
1st	3.75
2nd	2.00
3rd	1.34
4th	1.00
5th	0.77
6th	0.63
Reverse	3.54
Axle ratios	3.42, 3.73, 4.10
PTO	Left -or right-side with split shaft capability

TRANSFER CASES: BW 44-46, BW 44-47

Availability	Optional on 6.7-litre diesel and 6.4-litre HEMI V8
Type	Part-time – BW 44-47 manual shift and BW 44-46 electric shift
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Low-range Ratio	2.64
Center Differential	None

**AXLES**

See Feature Availability chart

ELECTRICAL SYSTEM

See Feature Availability chart

SUSPENSION

Front	Three-link with track bar, coil springs, stabilizer bar, twin-tube shock absorbers, solid axle
Rear	Hotchkiss leaf spring suspension, solid axle

BRAKES

Front	360 x 39 (14.2 x 1.5) vented disc with twin 60 (2.4) piston caliper
Rear	358 x 34 (14.1 x 1.3) vented disc with twin 45 (1.8) piston caliper for SRW, 51 (2.0)r DRW
Power-assist	Hydroboost

AIR BAGS

Regular Cab	2
Crew Cab	2

STEERING

Power-assist	Hydraulic assist
--------------	------------------

DIMENSIONS AND CAPACITIES

Regular Cab 364.4 cm (143.5-in.) WB, 152.4 cm (60-in.) CA SRW	4x2	4x4
Wheelbase	3,645 (143.5)	3,644 (143.5)
Turning diameter – m (ft)	45.0 (13.7)	55.5 (16.9)
Track Width – Front	1,930 (76.0)	1,930 (76.0)
Track Width – Rear	1,869 (73.6)	1,869 (73.6)
Overall Length	5,952 (234.3)	5,952 (234.3)
Overall Width @ Single Ground Reference Point (SgRP) Front	2,004 (78.9)	2,004 (78.9)
Overall Height	2,035 (80.1)	2,035 (80.1)
Suspension or Axle to Ground – Front	262 (10.3)	221 (8.7)
Suspension or Axle to Ground – Rear	213 (8.4)	213 (8.4)
Approach Angle (degrees)	28.3	28.3



2017 RAM COMMERCIAL 3500 CHASSIS CAB CANADIAN SPECIFICATIONS



Ramp Breakover Angle (degrees)	23.7	23.7
Departure Angle (degrees)	31.1	31.1
Regular Cab 364.4 cm (143.5-in.) WB, 152.4 cm (60-in.) CA DRW		
	4x2	4x4
Wheelbase	3,645 (143.5)	3,645 (143.5)
Turning diameter – m (ft)	45.0 (13.7)	55.5 (16.9)
Track Width – Front	1,930 (76.0)	1,930 (76.0)
Track Width – Rear	1,869 (73.6)	1,869 (73.6)
Overall Length	5,952 (234.3)	5,952 (234.3)
Overall Width @ Single Ground Reference Point (SgRP) Front	2,004 (78.9)	2,004 (78.9)
Overall Height	2,035 (80.1)	2,035 (80.1)
Suspension or Axle to Ground – Front	262 (10.3)	221 (8.7)
Suspension or Axle to Ground – Rear	213 (8.4)	213 (8.4)
Approach Angle (degrees)	28.3	28.3
Ramp Breakover Angle (degrees)	23.7	23.7
Departure Angle (degrees)	31.1	31.1
Regular Cab 425.4 cm (167.5-in.) WB, 213.3 cm (84-in.) CA DRW		
	4x2	4x4
Wheelbase	4,255 (167.5)	4,255 (167.5)
Turning diameter – m (ft)	51.8 (15.8)	51.8 (15.8)
Track Width – Front	1,930 (76.0)	1,930 (76.0)
Track Width – Rear	1,869 (73.6)	1,869 (73.6)
Overall Length	6,561 (258.3)	6,561 (258.3)
Overall Width @ Single Ground Reference Point (SgRP) Front	2,004 (78.9)	2,004 (78.9)
Overall Height	2,032 (80.0)	2,032 (80.0)
Suspension or Axle to Ground – Front	262 (10.3)	221 (8.7)
Suspension or Axle to Ground – Rear	213 (8.4)	213 (8.4)
Approach Angle (degrees)	28.4	28.4
Ramp Breakover Angle (degrees)	20.8	20.8
Departure Angle (degrees)	31.0	31.0



2017 RAM COMMERCIAL 3500 CHASSIS CAB
**CANADIAN
 SPECIFICATIONS**



Crew Cab 437.8 cm (172.4-in.) WB, 152.4 (60-in.) CA DRW	4x2	4x4
Wheelbase	4,379 (172.4)	4,379 (172.4)
Turning diameter m (ft)	53.2 (16.2)	53.2 (16.2)
Track Width – Front	1,930 (76.0)	1,930 (76.0)
Track Width – Rear	1,869 (73.6)	1,869 (73.6)
Overall Length	7,170 (282.3)	7,170 (282.3)
Overall Width @ Single Ground Reference Point (SgRP) Front	2,004 (78.9)	2,004 (78.9)
Overall Height	2,030 (79.9)	2,030 (79.9)
Suspension or Axle to Ground – Front	262 (10.3)	224 (8.8)
Suspension or Axle to Ground – Rear	213 (8.4)	213 (8.4)
Approach Angle (degrees)	28.5	28.5
Ramp Breakover Angle (degrees)	18.2	18.2
Departure Angle (degrees)	30.9	30.9

(a) Turning diameter is measured at the outside of the tires at curb height. Turning diameters and steering wheel turns, lock-to-lock may differ with optional tires and wheels.

ACCOMMODATIONS

Model	Regular Cab	Crew Cab
Seating Capacity, F/R	3/0 or 2/0	3/3 or 2/3
Front		
Headroom	1,014 (39.9)	1,044 (41)
Legroom	1,041 (41)	1,041 (41)
Shoulder Room	1,676 (66)	1,676 (66)
Hip Room	1,599 (62.9)	1,605 (63.2)
Seat Travel	230 (9)	230 (9)
Recliner Range (degrees)	85 (38 RWD, 47 FWD)	56 (38 RWD, 18 FWD)
Rear		
Headroom	N/A	1,014 (39.9)
Legroom	N/A	1,023 (40.3)
Shoulder Room	N/A	1,669 (65.7)
Hip Room	N/A	1,605 (63.2)
Interior Volume		
Front – litres (cu. ft.)	1,770 (62.5)	1,818 (64.2)
Rear – litres (cu. ft.)	N/A	1,730 (61.1)

